

South Florida Water Management District

3301 Gun Club Road, West Palm Beach, Florida 33406 • (561) 686-8800 • FL WATS 1-800-432-2045 TDD (561) 697-2574

RES 14

RECEIVED

MAR 15 1999

MEMORANDUM

EVERGLADES REGULATION

TO:

SFWMD/Seminole Agreement Working Group

THROUGH:

Leslie A. Wedderburn, Director, Water Resources Evaluation Department

Linda J. Lindstrom, Director, Resource Assessment Division, WRE

FROM:

Tim Bechtel, Sr. Supervising Environmental Scientist,

Resource Assessment Division, WRE

Cheol Mo, Sr. Environmental Scientist,

Resource Assessment Division, WRE

CM

ĎATE:

March 8, 1999

SUBJECT:

Final Fourth Semiannual Progress Report - May 1, 1998 to October 30, 1998

The enclosed fourth semiannual progress report has been prepared in accordance with the SFWMD/Seminole Tribe Agreement, Paragraph A.3. The report presents the data collected and the results obtained from the total phosphorus load calculations for the period May 1, 1998 through October 30, 1998.

Please contact Tim Bechtel if you have any questions or suggestions regarding this final report.

Attachment CM/TB/dwp

)

Fourth Semiannual Progress Report

Total Phosphorus Load Calculations for Sites Stipulated in the SFWMD/Seminole Tribe Agreement

For the Period of May 1, 1998 through October 31, 1998

By

Timothy J. Bechtel, Ph.D., Sr. Supv. Environmental Scientist and Cheol Mo, Ph.D., Sr. Environmental Scientist

March 8, 1999

Resource Assessment Division
Water Resources Evaluation Department
South Florida Water Management District
West Palm Beach, Florida

Submitted to

SFWMD/Seminole Tribe Agreement Working Group

•

Table of Contents

| | | Page |
|-----------------|---|------|
| List of Figures | | ii |
| List of Tables. | | iii |
| Introduction | | 1 |
| Methods | | 3 |
| Results of Pho | sphorus Load Calculations | 5 |
| Results of Flov | w Comparisons | 27 |
| Water Quality | Data | 33 |
| Appendix I. | Flow Chart for Water Flow and Water Quality Data Collected for the SFWMD/Seminole Cooperative Agreement | 45 |
| Appendix II. | SFWMD/Seminole Agreement Sampling Station Names | 47 |
| Appendix III. | Total Phosphorus (TP) Data for the Period of May 1,1998 through October 31, 1998 | 49 |
| Addendum: | L28IS Nutrient, Water Quality and Flow Data Summary for the Period of March 1, 1998 through September 30, 1998 | |

List of Figures

| Figure | | Page |
|--------|--|------|
| 1 | SFWMD/Seminole Agreement Water Quality and Flow Sampling Sites | 4 |
| 2 | L3BRS TP Load, Flow and TP Concentration | 8 |
| 3 | USSO TP Load, Flow and TP Concentration | 9 |
| 4 | L28U Flow | 10 |
| 5 | S140 TP Load, Flow and TP Concentration | 11 |
| 6 | WWEIR TP Load, Flow and TP Concentration | 14 |
| 7 | NFEED TP Load, Flow and TP Concentration | 13 |
| 8 | S190 TP Load, Flow and TP Concentration | 14 |
| 9 | L28IN Flow | 15 |
| 10 | L28IS Flow | 15 |
| 11 | Comparison of WFEED, NFEED, and S190 Flows | 29 |
| 12 | Relationship between L28IN Flow and L28IS Flow | 30 |
| -13 | Comparison of L28IN and L28IS Flows with S190 Flow | 31 |
| 14 | Comparison of L28U Flow with USSO Flow | 32 |
| 15 | Comparison of TN Concentrations and Median Values | 35 |
| 16 | Comparison of TP Concentrations and Median Values | 36 |

List of Tables

| Table | | Page |
|-------|--|------|
| 1 | Seminole/SFWMD Agreement Total Phosphorus (TP) Concentration and and Water Flow Data Summary for the Period of May 1, 1998 through October 31, 1998 | 17 |
| 2 | L28IN, L28IS, and L28U Flow Data Summary for the Period of May 1, 1998 through September 30, 1998 | 23 |
| 3 | Seminole/SFWMD Agreement Total Phosphorus (TP) Load and Flow Summary for the Period of May 1998 through October 1998 | 24 |
| 4 | Seminole/SFWMD Agreement Monthly Total Phosphorus (TP) Load and Monthly Flow Summary by Station Name for the Period of May 1998 through October 1998 | 25 |
| 5 | Summary of Water Quality Parameters Collected by Grab Sampling at Station L3BRS for the Period of May 1998 through October 1998 | 37 |
| 6 | Summary of Water Quality Parameters Collected by Grab Sampling at Station USSO for the Period of May 1998 through October 1998 | 38 |
| 7 | Summary of Water Quality Parameters Collected by Grab Sampling at Station S140 for the Period of May 1998 through October 1998 | 39 |
| 8 | Summary of Water Quality Parameters Collected by Grab Sampling at Station WWEIR for the Period of May 1998 through October 1998 | 40 |
| 9 | Summary of Water Quality Parameters Collected by Grab Sampling at Station NFEED for the Period of May 1998 through October 1998 | 41 |
| 10 | Summary of Water Quality Parameters Collected by Grab Sampling at Station S190 for the Period of May 1998 through October 1998 | 42 |
| 11 | Trace Metal Concentrations above the Detection Limit | 43 |

Introduction

The Agreement between the South Florida Water Management District (the District) and the Seminole Tribe of Florida (the Seminole Tribe), executed on January 17, 1996, requires periodic monitoring of the quality of surface water entering, originating on and leaving the Big Cypress Seminole Indian Reservation (the Reservation) to ensure compliance with applicable water quality standards imposed by law and that the overall surface water quality within the Reservation is not adversely impacted.

Pursuant to the Agreement, the District, with the cooperation of the Seminole Tribe, initiated a water quality monitoring program in June of 1996. To help the SFWMD/Seminole Agreement Working Group track the results and progress of this monitoring effort, the District prepares a semiannual report that summarizes and analyzes the water quality and flow data collected since the implementation of the program.

The fourth semiannual progress report covers the wet season of 1998. This report presents the results of TP load calculations for the period of May 1, 1998, through October 31, 1998, for the following six sites the District monitors: North Feeder Canal (NFEED), West Feeder Canal (WWEIR), S190 Spillway (S190), L3 Canal Sampling Station (L3BRS/USL3BRS), U.S. Sugar Outfall (USSO) from the C-139 Annex, and the S140 Pump Station Complex (S140). The summary of the USGS flow data for L28U, L28IN and L28IS from May 1, 1998, through September 30, 1998, is also presented in this report and comparisons of the flow measured at the L28I and L28U canal sites to the flows measured by the District at upstream sites are presented.

The United States Geological Survey (USGS) has been collecting the flow data at the L28IN, L28IS and L28U sites since March 1, 1997. The Seminole Tribe began their water quality and nutrient data collection at L28 Interceptor Canal North (L28IN) and L28 Canal Upstream (L28U) sites on August 21, 1997. However, the quality control/quality assurance procedures for the sites are under review and the nutrient data were not ready for this report. Water quality data for the Miccosukee Tribe site, L28 Interceptor Canal South (L28IS) are presented as an addendum to this report because the data were not available at the time the draft report was prepared.

All water quality data collected from May 1, 1998, through October 31, 1998, at the six sites monitored by the District are summarized in Table 5 through Table 10. Each water quality parameter measured at the six sites was compared with the Class III Standard (Florida Administrative Code 62-302.530, Criteria for Surface Water Quality Classifications) and the Sub-Class 2-B Criteria (Seminole Tribe of Florida, Water Quality Standards for the Big Cypress Indian Reservation) to see if any criterion had been exceeded.

One copper and two zinc measurements were above the detection limit but did not exceed the Class III Criteria. Only one iron measurement exceeded the Class III Criterion (Table 11). The standards for the trace metals, cadmium, copper, lead, and zinc are a function of water hardness. Hardness is calculated using the magnesium and calcium concentrations of the same water sample used to measure the trace metals (Standard Method 19th Ed., 2340 B., p2-36, 1995). Except for periodic low dissolved oxygen

(D.O.) concentrations at some sites, and an iron measurement at L3BRS on October 8, 1998, no Class III Criteria were exceeded during this reporting period.


Water quality monitoring at WFEED, the sampling station located upstream of the weir in the West Feeder Canal, was discontinued as of August 27, 1998, because it was concluded that the samples at the weir sampling site, WWEIR, provide better representative water quality data for the West Feeder Canal.

Methods

Figure 1 is a location map showing the water quality sampling and flow measurement sites that were established for the Agreement. The NFEED, WWEIR, USSO, L3BRS/USL3BRS, S190 and S140 sites are maintained and sampled by the District. The NFEED, USSO, and L3BRS/USL3BRS sites are equipped with ultrasonic velocity meters (UVMs) to measure flow and auto-samplers to collect flow proportional water quality samples. The WWEIR site uses a weir equation to calculate flow and trigger an auto-sampler. Grab samples are also collected at the NFEED, WWEIR, USSO, L3BRS/USL3BRS sites to supplement the auto-sampler data. Flow through S190 and S140 is calculated using structure-specific equations. At both S190 and S140 water quality data are collected by grab sampling procedures. The sites at L28IN and L28U are equipped with UVMs installed and maintained by the USGS and auto-samplers supplied and operated by the Seminole Tribe. The Miccosukee Tribe has a monitoring site located at L28IS, which is equipped with a UVM supplied by the USGS and a Tribe-owned auto-sampler.

Graphs for the six sites monitored by the District summarizing daily mean flows expressed in cubic feet per second (cfs), TP concentrations in parts per billion (ppb), and resulting daily TP loads in kilograms (kg) are presented in Figure 2 through Figure 7. The graphs summarizing the daily mean flows, expressed in cubic feet per second (cfs), for the three sites monitored by the U.S.G.S. are presented in Figure 8 through Figure 10. Note that the same scales for the flows, TP concentrations, and TP loads are used in all nine figures, except for the TP load at L3BRS, to make comparisons easy.

Figure 1: SFWMD/Seminole Agreement Water Quality and Flow Sampling Sites



- Grab samples and flow through structures
- Autosamplers and flows from UVMS



Results of Phosphorus Load Calculations

The results of the water flow analyses and the computed total phosphorus loads for the period of May 1, 1998, through October 31, 1998, at sites WWEIR, NFEED, USSO, L3BRS/USL3BRS, S190, and S140 are presented in Tables 1. These data were used to create the total phosphorus load graphs for the sites. The results of the water flow analyses for the period of May 1, 1998, through September 30, 1998, at sites L28IN, L28IS, and L28U are also presented in Table 2. Because the water quality data for L28IN, L28IS, and L28U are not available for this period, only flow data are reported. Table 3 summarizes the monthly flows, total phosphorus loads, and total phosphorus flow-weighted mean concentrations at the District's six sites and the monthly flows for the other three sites.

There are usually heavy rainfalls during the summer months followed by relatively dry periods during winter months in South Florida. The amount of TP load is mainly governed by the amount of rainfall and consequential flows. The TP loads in the reporting area had been following the similar pattern, peaking during the wet season and remaining low during the dry season. However, there have been exceptionally heavy rainfalls and, thus, heavy flows at canals during the last dry season (October, 1997 through April, 1998) followed by an exceptionally dry "wet season." There was exceptionally low or no flow until mid July throughout the area. Only September and October showed substantial flow and TP loads during the reporting period. The total flow at L3BRS was the highest among the nine sites. It was about a third higher than the total flow at S190, the site with the second biggest flow. The TP concentrations at L3BRS were much higher than the TP concentrations at other sites and, consequently, the TP load at L3BRS was the biggest among the six sites, whose TP concentrations were reported. The TP load at L3BRS was almost four times larger than the TP load at S190, the site with the second biggest TP load.

L3BRS

Flow at L3BRS had been very low until mid July (1, 1 and 7 thousand acre-feet in May, June and July, respectively) but increased to 28 thousand acre-feet in September. The total flow for May 1, 1998, through October 31, 1998, was 82 thousand acre-feet, the largest of the all nine sites. The TP load peaked at 6,778 kg in September 1998. The sum of the TP loads at L3BRS in September and October was 11,502 kg and that is close to four times larger than the TP load for the entire period at WWEIR and NFEED. The total load for the entire reporting period was 14,350 kg, the largest among the six sites. The associated flow-weighted mean concentration of the total phosphorus data collected by the auto-sampler was 175 ppb, the highest among the six sites. The results for L3BRS are presented in Figure 2.

USSO

The total flow for the period was 18 thousand acre-feet, much lower than that at L3BRS. The total phosphorus load for the reporting periods calculated by the auto-sampler composite TP concentrations was 2,111 kg (Figure 3). The flow-weighted mean concentration of the auto-sampler data collected for the period was 113 ppb.

L28U

The flow data for L28U from May 1, 1998 to September 31, 1998 are presented in Figure 4. Total flow was for the period (May 1 to September 31) was 39 thousand acre-feet. This was more than twice of 15 thousand acre-feet at USSO for the same period.

S140

The total phosphorus load calculated for S140 for the period of May 1, 1998, through October 31, 1998, was 3,761 kg. During the 184 day period, 81 days had no positive flow. The total flow for the period was 66 thousand acre-feet. For the period of May 1 through September 30, total flow was 50 thousand acre-feet, which is 11 thousand acre-feet more than the total flow at L28U.

The load estimate is based on the grab samples collected during flow events (Figure 5). The associated flow-weighted mean concentration of total phosphorus was 52 ppb, considerably lower than that of USSO (145 ppb). The low TP concentration at S140 compared to the TP concentration at USSO and the high flow volume compared to the total flow at L28U indicates that (1) S140 may get much of the water from south, and (2) the TP concentration of the water from the south is very low.

WWEIR

There had been no flow in the West Feeder Canal from late April until mid-July and, after that, the flow was low until late August. The flow peaked in late September. There were 78 days with no flow during the reporting period of May 1, 1998, through October 31, 1998 (total 184 days).

The TP load discharged from the West Feeder Canal, calculated using the auto-sampler TP data at WWEIR, from May 1, 1998 through October 31, 1998 was 1,042 kg (Figure 6). The flow-weighted mean concentration of total phosphorus was 62 ppb. The total phosphorus load calculated for S190 for the reporting period was 6,988 kg with total flow of 17 thousand acre-feet.

NFEED

There had been no substantial flow in the North Feeder Canal until early August but the flow data showed that there were very small but continuous upward (negative) and downward (positive) flow of the water flow during that period. At times of discharge through S190 both positive and negative flows can occur at the NFEED UVM site. However, the oscillating velocities measured by the UVM were probably caused by a circulation pattern that translated into positive and negative flows when there was no net discharge past the UVM site because the gates at S190 were closed. Both positive and negative flows and the associated positive and negative total phosphorus loads are reported in this report.

The flow-weighted mean concentration of total phosphorus data collected by the auto-sampler was 87 ppb. For the period, total positive flow was 7 thousand acre-feet and TP load was 730 kg (Figure 7). Total negative flow was 2 thousand acre-feet and the reverse TP load associated with that negative flow was 170 kg. During the last reporting period, May 1, 1997, through April 30, 1998, the TP load at NFEED was much higher than that

at WWEIR despite the total flow was much smaller. The TP concentration at NFEED had been much higher (146 ppb) than that at WWEIR (32 ppb). For the present reporting period of May 1, 1998, through October 31, 1998, the TP load at NFEED was lower than that at WWEIR. The total flow at North Feeder Canal was about two fifth of the total flow at West Feeder Canal and the difference in the TP concentrations for the two sites was not as big as it had been for the last reporting period.

S190

The gates at S190 were closed except for occasional brief maintenance openings until early August. The load estimate is based on the grab samples collected during flow events (Figure 8). The flow-weighted mean TP concentration at S190, which is fed by West Feeder Canal and North Feeder Canal, was 63 ppb, which is closer to WWEIR value than to NFEED value. The total phosphorus load calculated for S190 for the reporting period was 1,355 kg. The total flow was 22 thousand acre-feet. Both the TP load and the total flow at S190 were very comparable to the sum of the North and West Feeder Canals.


L28IN


The daily flow at L28IN for the period of May 1, 1998, through September 30, 1998, is presented in Figure 9. Total flow for the period was 16 thousand acre-feet. For the last reporting period, the total flow at L28IN was about 20 thousand acre-feet lower than the total flow at S190 or L28IS. For the present reporting period, the total flow at L28IN was about 6 thousand acre-feet lower than the total flow at S190 and was about 4 thousand acre-feet lower than the total flow at L28IS. There was almost 7 thousand acre-feet of negative (reverse) flow for the present period.


L28IS


Water quality data were not available for this report. Total flow at L28IS for the period of May 1, 1998, through September 30, 1998, was 20 thousand acre-feet, comparable to the total flow at S190 (Figure 10).


ть соис. (ррь) Figure 2. L3BRS TP Load, Flow and TP Concentration 100 500 001 300 ↔ Grab TP w/o flow Daily Mean Flow Autosampler TP Daily TP Load ♦ Autosampler
⊕ Grab TP w/ 1000 009 00₺ 200 009 FLOW (cfs) TP LOAD (kg)

















Figure 10. L28IS FLOW 001 200 008 009 FLOW (cfs)

Table 1. Seminole/SFWMD Agreement total phosphorus (TP) data and water flow data summary for the period of May 1, 1998 through October 31, 1998.

For L3BRS:

```
term
        clab
                glab
                        qlab
                                dbkey qsign itype ldsign iymdcomp
L3BRS
        USL3BRS L3BRS
                       L3BRS_O 16245
                                      1 1
Grab sample n = 10
    first datum :
                   1998/05/21
    last datum :
                   1998/10/22
    average value (arithmetic mean) = 143.5 ppb
    range = 53 to 204 ppb
   note: duplicate data in grab sample on 1998/05/21
Grab sample w/ + flow = 10
    first datum :
                   1998/05/21
   last datum :
                   1998/10/22
    average value (arithmetic mean) = 143.5 ppb
    range = 53 to 204 ppb
    flow weighted mean for data w/ +flow = 178.5 ppb
    regression: TP conc (ppb) = 116.3994 + 0.1197 * flow (cfs)
    load ratio of comp:grab = 1.02438 (common days = 10)
Autosampler (flow proportional composite) n = 24
    first datum :
                   1998/05/07
    last datum :
                   1998/11/04
    average value (arithmetic mean) = 128.1 ppb
   range = 42 to 213 ppb
    flow weighted mean for data = 175.4 ppb
   regression: TP conc (ppb) = 95.4672 + 0.1714 * flow (cfs)
Flow data:
   number of no flow days = 0
   number of positive flow days = 184
   total flow = 33395.961 cfs-d
   number of negative flow days = 0
   no missing flow data
```

number of negative flow days = 1 total negative flow = -0.080 cfs-d

no missing flow data

For USSO:

```
term
        clab
                glab
                        σlab
                                dbkey qsign itype ldsign iymdcomp
USSO
        USSO
                USSO
                        USSO_O
                                16749 1
                                         1
                                                0
 Grab sample n = 14
    first datum :
                    1998/05/21
    last datum :
                   1998/10/22
    average value (arithmetic mean) = 106.1 ppb
    range = 33 to 227 ppb
    note: duplicate data in grab sample on 1998/06/03
    note: a grab sample datum, 788 ppb on 1998/06/25 is considered to be
         an outlier and excluded in the calculations.
Grab sample w/ + flow = 14
    first datum :
                   1998/05/21
    last datum :
                   1998/10/22
    average value (arithmetic mean) = 106.1 ppb
    range = 33 to 788 ppb
    flow weighted mean for data w/ +flow = 112.9 ppb
    regression: TP conc (ppb) = 94.3037 + 0.2956 * flow (cfs)
    load ratio of comp:grab = 01.02492 (common days = 8)
   note: the outlier, 788 ppb on 1998/06/25 is excluded.
Autosampler (flow proportional composite) n = 18
    first datum :
                   1998/05/07
   last datum :
                    1998/11/04
   average value (arithmetic mean) = 116.7 ppb
   range = 47 to 343ppb
   flow weighted mean for data = 112.7 ppb
   regression: TP conc (ppb) = 125.4830 - 0.1894 * flow (cfs)
   note: no composite sample after 1998/05/21 for 35 days
         no composite sample after 1998/09/22 for 9 days
Flow data:
   number of no flow days = 1
   number of positive flow days = 182
   total positive flow = 7474.681 cfs-d
```

For S140:

term clab glab qlab dbkey qsign itype ldsign iymdcomp S140 NONE S140 S140_T 06754 1 0 0

Grab sample n = 9

first datum : 1998/05/21 last datum : 1998/11/04

average value (arithmetic mean) = 53.7 ppb

range = 30 to 77 ppb

Grab sample w/ + flow = 6

first datum : 1998/07/01 last datum : 1998/10/22

average value (arithmetic mean) = 52.7 ppb

range = 30 to 77 ppb

flow weighted mean for data w/ +flow = 51.7 ppb

regression: TP conc (ppb) = 63.3170 - 0.0425 * flow (cfs)

Flow data:

number of no flow days = 81 number of positive flow days = 100 total positive flow = 27132.102 cfs-d number of negative flow days = 3 total negative flow = -4.220 cfs-d no missing flow data

For WWEIR:

```
term
       clab
               glab
                       glab
                               dbkey qsign itype ldsign iymdcomp
WWEIR
       WWEIR
               WWEIR
                       WFEED_O 16752 1 2
                                               0
                                                       19971224
Grab sample n = 27
   first datum :
                   1998/05/07
   last datum :
                   1998/11/04
   average value (arithmetic mean) = 45.5 ppb
   range = 15 to 88 ppb
Grab sample w/ + flow = 15
   first datum :
                   1998/07/23
   last datum :
                   1998/10/28
   average value (arithmetic mean) = 42.2 ppb
   range = 15 to 88 ppb
   flow weighted mean for data w/ +flow = 59.6 ppb
   regression: TP conc (ppb) = 15.7826 + 0.4478 * flow (cfs)
   load ratio of comp:grab = 0.941257 (common days = 14)
Autosampler (flow proportional composite) n = 14
   first datum : 1998/07/23
   last datum :
                   1998/11/04
   average value (arithmetic mean) = 47.6 ppb
   range = 19 to 98 ppb
   flow weighted mean for data = 61.8 ppb
   regression: TP conc (ppb) = 30.5027 + 0.2464 * flow (cfs)
   note: no composite sample after 1998/08/27 for 77 days
         no composite sample after 1998/07/30 for 14 days
Flow data:
   number of no flow days = 78
   number of positive flow days = 106
   total flow = 6895.669 cfs-d
   number of negative flow days = 0
   no missing flow data
```

For NFEED:

```
term
        clab
                glab
                        qlab
                                dbkey qsign itype ldsign iymdcomp
NFEED
        NFEED
                NONE
                        NFEED_O 16754 1
                                           1
Grab sample n = 27
   first datum :
                   1998/05/07
   last datum :
                   1998/11/04
  average value (arithmetic mean) = 83.4 ppb
  range = 31 to 194 ppb
Grab sample w/ +flow = 16
   first datum : 1998/05/07
   last datum : 1998/10/08
   average value (arithmetic mean) = 78.4 ppb
   range = 31 to 194 ppb
   flow weighted mean for data w/ +flow = 108.2 ppb
   regression: TP conc (ppb) = 33.7176 + 2.1841 * flow (cfs)
   load ratio of comp:grab = 1.03015 (common days = 16)
Autosampler (flow proportional composite) n = 27
   first datum :
                  1998/05/07
   last datum :
                   1998/11/04
   average value (arithmetic mean) = 86.7 ppb
   range = 33 to 187 ppb
   flow weighted mean for data = 111.3 ppb
   regression: TP conc (ppb) = 59.7681 + 1.8208 * flow (cfs)
Flow data:
  number of no flow days = 0
  number of positive flow days = 121
  total positive flow = 2675.729 cfs-d
  number of negative flow days = 62
  total negative flow = -664.590 cfs-d
  1 missing flow data on 1998/10/01
```

For S190:

```
term
       clab
               glab
                       qlab
                               dbkey qsign itype ldsign iymdcomp
                       S190_S 15987 1 0 0
S190
       NONE
               S190
Grab sample n = 7
   first datum : 1998/05/21
   last datum : 1998/10/08
   average value (arithmetic mean) = 63.0 ppb
   range = 22 to 139 ppb
Grab sample w/ +flow = 5
   first datum : 1998/07/30
   last datum : 1998/10/08
   average value (arithmetic mean) = 54.4 ppb
   range = 22 to 85 ppb
   flow weighted mean for data w/ +flow = 62.5 ppb
   regression: TP conc (ppb) = 36.1546 + 0.2167 * flow (cfs)
Flow data:
   number of no flow days = 102
   number of positive flow days = 82
   total flow = 9007.550 cfs-d
   number of negative flow days = 0
   no missing flow data
```

Table 2. Seminole/SFWMD Agreement water flow data summary for the period of May 1, 1998 through September 30, 1998.

For L28IN:

dbkey qsign itype ldsign iymdcomp clab term glab qlab 0 1 L28IN_O FF809 1 L28IN L28IN BSC5 Flow data from 1998/05/01 to 1998/09/30: number of no flow days = 0 number of positive flow days = 79 total flow = 6625.250 cfs-d number of negative flow days = 74 total flow = -2814.700 cfs-d no missing flow data

For L28IS:

term clab glab qlab dbkey qsign itype ldsign iymdcomp L28IS L28IG175 L28IS_0 FF812 1 1 0

Flow data from 1998/05/01 to 1998/09/30:
number of no flow days = 0
number of positive flow days = 90
total flow = 8181.780 cfs-d
number of negative flow days = 63
total flow = -2770.900 cfs-d
no missing flow data

For L28U:

term clab glab qlab dbkey qsign itype ldsign iymdcomp L28U L28U BCS7 L28U O FF808 1 1 0 19970917

Flow data from 1998/05/01 to 1998/09/30:
number of no flow days = 0
number of positive flow days = 151
total flow = 16102.000 cfs-d
number of negative flow days = 2
total flow = -3.560 cfs-d
no missing flow data

Table 3. Seminole/SFWMD Agreement TP load calculation summary: Total TP Load and Total Flow.

For positive flow:

| Term L3BRS | Period 5/1/1998-10/31/199 | TP Data Used 8 auto only (grab only | Flow (kacft) 81.706 | Load(kg) 14350 14292) |
|---------------|------------------------------|--|------------------------|------------------------------------|
| USSO | 5/1/1998-10/31/199 | 8 auto only (grab only | 18.287 | 2111 1914) |
| L28U | 5/1/1998- 9/30/199 | 8 Not Available | 39.395 | N/A |
| S140 | 5/1/1998-10/31/199 | 8 grab only | 66.381 | 3761 |
| WWEIR | 5/1/1998-10/31/199 | 8 auto only (grab only | 16.871 | 1042 1034) |
| NFEED | 5/1/1998-10/31/199 | 8 auto only (grab only | 6.546 | 730 661) |
| S190 | 5/1/1997-10/31/199 | 8 grab only | 22.038 | 1355 |
| L28IN | 5/1/1998- 9/30/199 | 8 Not Available | 16.209 | N/A |
| L28IS | 5/1/1998- 9/30/199 | 8 Not Available | 20.017 | N/A |

For negative (reverse) flow:

| Term L3BRS | Period 5/1/1998-10/31/1998 | TP Data Used auto only | Flow (kacft) 0.000 | Load (kg) 0 |
|---------------|-------------------------------|-------------------------|-----------------------|----------------|
| USSO | 5/1/1998-10/31/1998 | auto only (grab only | <0.001 | 0.1 |
| L28U | 5/1/1998- 9/30/1998 | Not Available | 0.009 | N/A |
| S140 | 5/1/1998-10/31/1998 | grab only | 0.010 | 0.6 |
| WWEIR | 5/1/1998-10/31/1998 | auto only | 0.000 | 0 |
| NFEED | 5/1/1998-10/31/1998 | auto only (grab only | 1.626 | 168 196) |
| S190 | 5/1/1997-10/31/1998 | grab only | 0.000 | 0 |
| L28IN | 5/1/1998- 9/30/1998 | Not Available | 6.886 | N/A |
| L28IS | 5/1/1998- 9/30/1998 | Not Available | 6.779 | N/A |

Table 4. Seminole/SFWMD Agreement total phosphorus (TP) load calculation monthly summary by station for the period of May 1, 1998 through October 31, 1998.

Note 1: Flow is in million cubic meters and in (thousand acre-feet).

Note 2: Flow-weighted mean concentration for each month is calculated by dividing monthly load with monthly total flow.

For L3BRS :

| | month da | ays | flow | load(Kg) fwmc(ppb) | flow_negative load_neg. |
|-------|-----------------|-----|-----------------|--------------------|---|
| L3BRS | 19 98/05 | 31 | 1.546 (1.254) | 116.930 75.619 | |
| L3BRS | 1998/06 | 30 | 1.589 (1.289) | 125.265 78.812 | • |
| L3BRS | 1998/07 | 31 | 8.102 (6.568) | 1144.204 141.232 | |
| L3BRS | 1998/08 | 31 | 34.757 (28.178) | 6777.766 195.005 | |
| L3BRS | 1998/09 | 30 | 25.478 (20.655) | 4724.777 185.447 | |
| L3BRS | 1998/10 | 31 | 10.234 (8.297) | 1461.259 142.788 | , |

For USSO:

| Station | month da | ays | flow | load(Kg) fwmc(ppb) | flow_negative load_neg. |
|---------|----------|-----|----------------|--------------------|---|
| USSO | 1998/05 | 31 | 0.223 (0.181) | 17.099 76.556 | - - |
| USSO | 1998/06 | 30 | 0.770 (0.624) | 227.676 295.829 | • • • • • |
| USSO | 1998/07 | 31 | 3.362 (2.725) | 356.935 106.183 | • |
| USSO | 1998/08 | 31 | 7.194 (5.832) | 732.406 101.810 | |
| USSO | 1998/09 | 30 | 4.243 (3.439) | 478.633 112.818 | , |
| USSO | 1998/10 | 31 | 2.497 (2.024) | 297.969 119.353 | |

For L28U:

| Station | month | đays | flow | load(Kg) | fwmc(ppb) | flow_negative load_neg |
|---------|---------|------|-----------------|----------|-----------|------------------------|
| L28U | 1998/05 | 31 | 2.291 (1.857) | | | -0.001 (-0.001) |
| L28U | 1998/06 | 30 | 3.198 (2.592) | | | -0.008 (-0.006) |
| L28U | 1998/07 | 31 | 7.319 (.5.934) | | | 0.000 (0.000) |
| L28U | 1998/08 | 31 | 15.213 (12.333) | | | 0.000 (0.000) |
| L28U | 1998/09 | 30 | 11.374 (9.221) | | | 0.000 (0.000) |

For S140 :

| Station | month d | lays | flow | load(Kg) fw | nc (ppb) | flow_negative lo | ad neg |
|---------|---------|------|-----------------|-------------|----------|------------------|--------|
| S140 | 1998/05 | 31 | 0.532 (0.431) | | | -0.002(-0.002) | -0.127 |
| S140 | 1998/06 | 30 | 0.555 (0.450) | | | | -0.431 |
| S140 | 1998/07 | 31 | 8.448 (6.849) | 521.759 | 61.759 | | 0.000 |
| S140 | 1998/08 | 31 | 20.167 (16.349) | 1471.492 | 72.967 | (0,000 (0,000) | 0.000 |
| S140 | 1998/09 | 30 | 20.883 (16.930) | 1075.160 | 51.485 | 0.000 (0.000) | 0.000 |
| S140 | 1998/10 | 31 | 15.796 (12.806) | 633.858 | 40.128 | 0.000 (0.000) | 0.000 |

For WWEIR :

| Station | month d | lays | flow | load(Kg) fwmc(ppb) | flow_negative load_neg |
|---------|---------|------|----------------|--------------------|------------------------|
| WWEIR | 1998/05 | 31 | 0.000 (0.000) | 0.000 | 0.000 (0.000) 0.000 |
| WWEIR | 1998/06 | 30 | 0.000 (0.000) | 0.000 | 0.000 (0.000) 0.000 |
| WWEIR | 1998/07 | 31 | 0.400 (0.325) | 13.851 34.597 | 0.000 (0.000) 0.000 |
| WWEIR | 1998/08 | 31 | 2.988 (2.423) | 98.643 33.011 | 0.000 (0.000) 0.000 |
| WWEIR | 1998/09 | 30 | 7.287 (5.908) | 550.714 75.571 | 0.000 (0.000) 0.000 |
| WWEIR | 1998/10 | 31 | 6.195 (5.022) | 379.183 61.210 | 0.000 (0.000) 0.000 |

For NFEED:

| Station | month d | lays | flow | load(Kg) fwmc(ppb) | flow_negative load_neg. |
|---------|---------|------|----------------|--------------------|-------------------------|
| NFEED | 1998/05 | 31 | 0.662 (0.537) | 40.800 61.623 | -0.112 (-0.091) -6.782 |
| NFEED | 1998/06 | 30 | 0.180 (0.146) | 8.182 45.465 | -0.111 (-0.090) -5.474 |
| NFEED | 1998/07 | 31 | 0.552 (0.448) | 34.183 61.872 | -0.242 (-0.197) -13.669 |
| NFEED | 1998/08 | 31 | 2.031 (1.647) | 233.646 115.033 | -0.186 (-0.151) -17.611 |
| NFEED | 1998/09 | 30 | 2.390 (1.938) | 323.354 135.292 | -0.192 (-0.156) -28.504 |
| NFEED | 1998/10 | 31 | 0.731 (0.592) | 90.265 123.537 | -0.782 (-0.634) -95.883 |

For \$190 :

| Station | month d | lays | flow | load(Kg) fwmc(ppb) | flow_negative load_neg. |
|---------|---------|------|----------------|--------------------|-------------------------|
| S190 | 1998/05 | 31 | 0.000 (0.000) | 0.000 | 0.000 (0.000) 0.000 |
| S190 | 1998/06 | 30 | 0.001 (0.000) | 0.011 22.000 | 0.000 (0.000) 0.000 |
| S190 | 1998/07 | 31 | 0.015 (0.012) | 0.329 22.000 | 0.000 (0.000) 0.000 |
| S190 | 1998/08 | 31 | 6.575 (5.330) | 351.094 53.399 | 0.000 (0.000) 0.000 |
| S190 | 1998/09 | 30 | 8.435 (6.838) | 446.405 52.923 | 0.000 (0.000) 0.000 |
| S190 | 1998/10 | 31 | 7.012 (5.685) | 557.008 79.434 | 0.000 (0.000) 0.000 |

For L28IN:

| Station | month | days | flow | load(Kg) | fwmc(ppb) | flow_negative | load_neg. |
|---------|---------|------|----------------|----------|-----------|---------------|-----------|
| L28IN | 1998/05 | 31 | 1.164 (0.943) | | | -1.938 (-1.57 | 1) |
| L28IN | 1998/06 | 30 | 1.089 (0.883) | | | -1.884 (-1.52 | 8) |
| L28IN | 1998/07 | 31 | 0.643 (0.521) | | | -1.896 (-1.53 | 7) |
| L28IN | 1998/08 | 31 | 6.217 (5.040) | | | -0.568 (-0.46 | 0) |
| L28IN | 1998/09 | 30 | 7.097 (5.753) | | • | -0.600 (-0.48 | 7) |

For L28IS :

| Station | month | days | flow | load(Kg) | fwmc(ppb) | flow_negative load_neg. | |
|---------|---------|------|---------|----------|-----------|-------------------------|--|
| L28IS | 1998/05 | 31 | 2.486 (| 2.016) | | -1.957 (-1.586) | |
| L28IS | 1998/06 | 30 | 2.068 (| 1.677) | | -1.862 (-1.509) | |
| L28IS | 1998/07 | 7 31 | 1.127 (| 0.914) | | -2.040 (-1.654) | |
| L28IS | 1998/08 | 3 31 | 6.460 (| 5.238) | | -0.548 (-0.444) | |
| L28IS | 1998/09 | 30 | 7.876 (| 6.385) | | -0.373 (-0.302) | |

Results of Flow Comparisons

Similarity of flow data at different sampling locations within a canal is one indication as to whether different measuring methods are providing essentially the same data.

West Feeder Canal, North Feeder Canal and S190

Because S190 is fed by the West and North Feeder Canals, the flow at S190 should be close to the sum of these two flows. The total flows matched closely and the graphs for the daily flows of the three sites and the sum of the West and North Feeder Canals show that the daily peaks also match well (Figure 11).

The magnitude of high peaks of the sum and the peaks of S190 flow matched well except for 4 occasions, showing that the calibration for NFEED flow calculations has been significantly improved. However, the problem with oscillation between positive and negative signals at NFEED during no net flow conditions when S190 was closed has not been completely resolved.

S190, L28IN and L28IS

Flow in the L28 Interceptor Canal is measured by the USGS at the southern boundary of the Big Cypress Seminole Indian Reservation (site L28IN) and at the western boundary of the Miccosukee Reservation (site L28IS). The S-190 spillway located within the Seminole Reservation is controlled by the District and determines the flow in the L28I Canal. Figure 12 shows that flow calibration at L28IN has been improved and the L28IN flow data is correlating well with the L28IS flow data for the present reporting period.

Figure 13 presents the flow data at these three sites from May 1, 1998 through September 30, 1998. It can be observed that the flows at L28IN and L28IS correlate very well with the flow from S-190 during the high flow period. However, both L28IN and L28IS flows show that the two fluctuated from about positive 100 cfs-day to about negative 100 cfs-day when S190 was closed. The daily records for L28IN and L28IS were so much in synchronization that it is hard to dismiss these signals simply as background noise. This phenomenon calls for further investigation.

L28U and USSO

In Figure 14 the L-28 Canal flow measured at the USSO site is compared with the flow measured at L28U. The highs and lows in the flow pattern correlate fairly well, but flow at L28U is more variable than the flow at USSO. Generally, the flow at L28U is higher than the flow at USSO with the difference becoming more prominent during high flow events. Sometimes L28U flow being more than two times higher than USSO flow on peak flow days. This observation suggests that there are inflows to the L28 Canal either from ground water seepage or surface inflow. It was not possible to compare the TP loads at the sites because the TP concentration data at L28U were not available for the reporting period. The flow data recorded at a UVM site, G89, which is located downstream from USSO and the G89 structure, were consistently between the USSO flow and L28IN flow. The G89 structure had been closed and, thus, there was no flow through the structure during the reporting period. A drainage channel had been identified between USSO and G89 UVM site, but the quantity and the nature of the flow at the channel has not measured yet.

These flow data may indicate that there is some additional water input to the system. There are eight identified inflows to the L-28 Canal between USSO and L28U. However, it should be emphasized that the differences among the daily flow data could merely reflect the inaccuracy of some data for one or more of the sites caused by bias or lack of calibration. It will be necessary to either calibrate the flow data or define the flow more accurately before a reliable total phosphorus load calculation can be made.






Figure 12. Relationship between L28IN Flow and L28IS Flow.





& 160 C PS: 1085.94 Por College &. (A) Figure 14. Comparison of L28U Flow with USSO Flow OC. ON BO φ⁰, **≤**∞ OG:ONE. 12 OS. On. 889 & Innie 86 Innas 0 OS INN OSSO Solution of BE MAN -L28U OS JUNE SES & Unr. & Stung. & S. TENISCO & S. T. E. W. C. C. OC. TOW.S! OS. TENY S. TOW. 250 200 9 350 900 150 100 -20 450 20 FLOW (cfs)

Note: G89 denotes the G89 UVM monitoring site, which is located downstream of USSO and the G89 Structure. The G89 Structure was closed and there was no flow through the structure for the reporting period.

Water Quality Data

Total phosphorus (TP) concentration data collected by both grab samples and autosamplers (Figure 15) and total nitrogen (TN) data calculated by the sum of total Kjeldahl nitrogen (TKN) and total nitrite and nitrate (NOX) (Figure 16) at the six sites, WWEIR, NFEED, S190, L3BRS, USSO, and S140 are presented as classic notched box plots. The narrowest part of the notch represents the median value for each site. The complete notch represents the lower and upper 95% confidence interval values. If the notches of two sites do not overlap, the respective site medians are significantly different at the 95% confidence level. The top and bottom sides of boxes represent the 75th and 25th percentiles, respectively. The whiskers show the range of values that fall within 1.5 times the absolute value of the difference between 75th and 25th percentiles. Values outside of the whiskers are plotted with asterisks if they do not exceed 3 times the absolute value of the difference between the 75th and 25th percentiles. Values beyond 3 times the absolute value are plotted with empty circles.

Figure 15 presents notched box plots for TP concentrations at the six District sampling sites. The TP concentration data from grab samples and auto-samplers were combined at sites where both sampling methods were used. The WWEIR site has the lowest TP concentrations of all sites. The median TP concentration at NFEED site was highest among the western sites but much lower than last reporting period. The differences in the median values among the three western sites are not significant for this reporting period. L3BRS has the highest TP concentrations among six sites, followed by USSO.

The notched box plots for total nitrogen concentrations are much more uniform among sites than TP concentrations (Figure 16). This may imply that TN has more natural sources and TP has more anthropologic sources but the results can not be interpreted until the variability of the nitrogen species comprising total nitrogen are evaluated for each site and compared.

The water quality data collected by grab sampling are summarized for each site in Tables 5 through 10. The tables are organized to present basic statistics for each parameter collected in accordance with Table 1.2 in the Standard Operating Procedures for Water Quality Collection in Support of the Big Cypress Seminole Indian Reservation Water Quality Agreement, Water Quality Monitoring Division, SFWMD, May 22, 1996, as well as the associated water quality criterion for those parameters listed in the table of Surface Water Quality Criteria, Chapter 62-302.530, F.A.C. and Table 12 of the Seminole Tribe's Water Quality Standards.

Comparison of the data with the criteria indicated that dissolved oxygen (D.O.) and total iron were the only parameters that exceeded their criteria. The dissolved oxygen exceedences occurred at all sites. D.O. is measured once per week when the autosamplers are serviced or grab samples collected during daylight hours. D.O. values, however, change throughout the day usually exhibiting highs in mid- to late afternoon and lows in early morning before sunrise. A variety of factors affect the D.O. concentration and the magnitude of the daily range. The values reported here are typical of Everglades Protection Area data from canals and marsh stations.

Most of the trace metal measurements for all sites, for cadmium, copper, lead, and zinc, were below the method detection limits (MDL). The three values measured above the detection limit during this reporting period are compared with the calculated criteria in Table 11. All measurements were below the criteria values, which are derived from the water hardness. The total iron concentration measured at L3BRS on October 8, 1998, exceeded 1 mg/L, the Class III Standard criterion for the metal. The high iron concentration, one of the major ions in the natural waters of South Florida, probably reflects the high clay mineral content in the sample.

Figure 15. Comparison of TN Concentrations and Median Values. USSO S190 L3BRS Stations **WWEIR NFEED** (J\gm) negortiN lstoT e, vi —




Table 5. Summary of Water Quality Parameters Collected by Grab Sampling at Station L3BRS for the Period from May 1998 through October 1998.

| Parameters | Mean | Range | Standard Deviation | Number of Samples | Criteria for Class III Predominantly Fresh Surface Waters, FAC 62-302 |
|------------------------------------|-------|---------------------------------------|-----------------------|--|---|
| Physical | | · · · · · · · · · · · · · · · · · · · | | | |
| Water Temperature (°C) | 29.5 | 27.0 - 31.9 | 1.6 | 9 | Not Applicable |
| Specific Conductance (µmhos/cm) | 469 | 331 - 566 | 83 | 9 | Not greater than 50% above background or 1,275 µmhos/cm |
| Total Suspended Solids (mg/L) | 13.0 | 3.0 - 23.0 | 14.1 | 2 | Not Applicable |
| Turbidity (NTU) | 3.3 | 0.8 - 13.0 | 3.7 | 9 | Less than or equal to 29 NTU above background |
| Dissolved Oxygen (mg/L) | 1.8 | 0.2 - 3.8 | 1.1 | 9 | Not be less than 5.0 mg/L |
| Dissolved Oxygen (% Saturation) | 22.7 | 2.9 - 48.1 | 14.0 | 9 | Not Applicable |
| Water pH | 7.2 | 6.7 - 7.5 | 0.3 | 9 | Not less than 6.0 or greater than 8.5 units |
| Apparent Color (PCU) | 151 | 62 - 223 | 63 | 9 | Not Applicable |
| Total Hardness (mg/L) | 159 | 155 - 163 | 6 | 2 | Not Applicable |
| Major ions | | | • | *************************************** | |
| Calcium (mg/L) | 54.7 | 53.6 - 55.7 | 1.5 | 2 | Not Applicable |
| Sodium (mg/L) | 31.6 | 27.0 - 36.2 | 6.5 | 2 | Not Applicable |
| Potaesium (mg/L) | 2.7 | 2.7 - 2.8 | 0.0 | 2 | Not Applicable ., |
| Magnesium (mg/L) | 5.5 | 5.2 - 5.9 | 0.5 | 2 | Not Applicable |
| Total Alkalinity (mg/L) | 160.2 | 114.5 - 190.6 | 28.0 | 9 | Not less than 20 mg/L |
| Sulfate (mg/L) | 8.0 | 7.3 - 8.6 | 0.9 | 2 | Not Applicable |
| Chloride (mg/L) | 41.9 | 22.7 - 54.7 | 11.5 | 9 | Not greater than 10% of background |
| Nutrients | | | | <u>. </u> | |
| Ammonium (mg/L) | 0.107 | <0.009 - 0.320 | 0.109 | 9 | Not Applicable |
| Nitrate+nitrite (mg/L) | 0.089 | 0.008 - 0.255 | 0.086 | 9 | Not Applicable |
| Total Nitrogen (mg/L) | 1.76 | 1.46 - 2.11 | 0.23 | 9 | Not Applicable |
| Orthophosphate (mg/L) | 0,099 | 0.028 - 0.166 | 0.045 | 9 | Not Applicable |
| Total Phosphorus (mg/L) | 0.148 | 0.045 - 0.204 | 0.053 | 9 | Not Applicable |
| Silica (mg/L) | 9,6 | 7.2 - 12.0 | 3.4 | 2 | Not Applicable |
| Trace Elements | | | | | |
| Arsenic (μg/L) | <1.5 | <1.5 - <1.5 | | 1 | Less than or equal to 50 µg/L |
| Cadmium (µg/L) | <0.3 | <0.3 - <0.3 | | 1 | Less than or equal to calculated valuusing: e ^{(@7082} (InH)-349) |
| Copper (µg/L) | 3,9 | 3.9 - 3.9 | | 1 | Less than or equal to calculated valuusing: e ^(0.8545[ht]-1.465) |
| lron (µg/L) | 996 | 882 - 1,110 | 161 | 2 | Less than or equal to 1,000 µg/L |
| Lead (µg/L) | <0.8 | <0.8 - <0.8 | | 1 | Less than or equal to calculated valuusing: e(1270[H]4,705) |
| Zinc (µg/L) | 6 | 6 - 6 | | 1 | Less than or equal to calculated valuusing: e(0.0473(nH)-0.7614) |

Table 6. Summary of Water Quality Parameters Collected by Grab Sampling at Station USSO for the Period from May 1998 through October 1998.

| Parameters | Mean | Rånge | Standard Deviation | Number of Samples | Criteria for Class III Predominantly Fresh Surface Waters, FAC 62-302 |
|------------------------------------|-------|----------------|-----------------------|----------------------|--|
| Physical | | | | | |
| Water Temperature (°C) | 28.8 | 27.1 - 30.3 | 0.9 | 12 | Not Applicable |
| Specific Conductance (µmhos/cm) | 537 | 462 - 618 | 46 | 12 | Not greater than 50% above background or 1,275 µmhos/cm |
| Total Suspended Solids (mg/L) | 6.5 | 3 - 10 | 4.9 | 2 | Not Applicable |
| Turbidity (NTU) | 4.1 | 1.0 - 16.6 | 4.5 | 10 | Less than or equal to 29 N I U above background |
| Dissolved Oxygen (mg/L) | 3.9 | 1.5 - 6.0 | 1,2 | 12 | Not be less than 5.0 mg/L |
| Dissolved Oxygen (% Saturation) | 49.4 | 18.9 - 73.5 | 15.2 | 12 | Not Applicable |
| Water pH | 7.2 | 6.7 - 7.5 | 0.3 | 12 | Not less than 6.0 or greater than 8.5 units |
| Apparent Color (PCU) | 109 | 74 - 140 | 24 | 10 | Not Applicable |
| Total Hardness (mg/L) | 226 | 219 - 232 | 9 | 2 | Not Applicable |
| Major lons | | | | | |
| Calcium (mg/L) | 82.9 | 80.4 - 85.3 | 3.5 | 2 | Not Applicable |
| Sodium (mg/L) | 25.8 | 24.9 - 26.7 | 1.3 | 2 | Not Applicable |
| Potassium (mg/L) | 5.4 | 5,3 - 5,6 | 0.2 | 2 | Not Applicable |
| Magnesium (mg/L) | 4.5 | 4.4 - 4.6 | 0.1 | 2 | Not Applicable |
| Total Alkalinity (mg/L) | 186.7 | 148.2 - 224.4 | 22.9 | 10 | Not less than 20 mg/L |
| Sulfate (mg/L) | 21.1 | 18.7 - 23.6 | 3.4 | 2 | Not Applicable |
| Chioride (mg/L) | 38.7 | 33.5 - 50.4 | 5.2 | 10 | Not greater than 10% of background |
| Nutrients | • | | | | # 17400 W |
| Ammonium (mg/L) | 0.074 | <0.009 - 0.165 | 0.059 | 12 | Not Applicable |
| Nitrate+nitrite (mg/L) | 0.023 | 0.005 - 0.148 | 0.042 | 11 | Not Applicable |
| Total Nitrogen (mg/L) | 1.62 | 1.33 - 2.27 | 0.26 | 12 | Not Applicable |
| Orthophosphate (mg/L) | 0.077 | 0.006 - 0.174 | 0.050 | 10 | Not Applicable |
| Total Phosphorus (mg/L) | 0.106 | 0.033 - 0.227 | 0.057 | 14 | Not Applicable |
| Silica (mg/L) | 10.4 | 9.6 - 11.3 | 1.2 | 2 | Not Applicable |
| Trace Elements | | | | | X (1) |
| Arsenic (μg/L) | <1.5 | <1.5 - <1.5 | | 1 | Less than or equal to 50 µg/L |
| Cadmium (µg/L) | <0.3 | <0.3 - <0.3 | | 1 | Less than or equal to calculated value using: e ^{(0.7882(nH]-0.49)} |
| Copper (µg/L) | <1.2 | <1.2 - <1.2 | | 1 | Less than or equal to calculated value using: e ^{(0.0545(h+f)-1.405)} |
| lron (μg/L) | 248 | 159 - 337 | 126 | 2 | Less than or equal to 1,000 µg/L |
| Lead (µg/L) | <0.8 | <0.8 - <0.8 | | 1 | Less than or equal to calculated value using: e ^{(1,2,73} (HH)-4,705) |
| Zinc (μg/L) | <4 | <4 - <4 | | -1 | Less than or equal to calculated value using: e ^{(0.0473(t-t)} (0.7814) |

Table 7. Summary of Water Quality Parameters Collected by Grab Sampling at Station S140 for the Period from May 1998 through October 1998.

| Parameters | Mean | Range | Standard Deviation | Number of Samples | Criteria for Class III Predominantly Fresh Surface Waters, FAC 62-302 |
|---------------------------------|-------|---------------------------|-----------------------|----------------------|---|
| Physical | | | | | |
| Water Temperature (°C) | 29.3 | 26.6 - 31.0 | 1.3 | 8 | Not Applicable |
| Specific Conductance (µmhos/cm) | 454 | 353 - 515 | 58 | 8 | Not greater than 50% above background or 1,275 µmhos/cm |
| Total Suspended Solids (mg/L) | <3 | <3 - <3 | | 2 | Not Applicable |
| Turbidity (NTU) | 1.7 | 0.8 - 2.4 | 0,6 | 8 | Less than or equal to 29 NTU above background |
| Dissolved Oxygen (mg/L) | 1.9 | 0.8 - 5.7 | 1.6 | 8 | Not be less than 5,0 mg/L |
| Dissolved Oxygen (% Saturation) | 24.6 | 10.0 - 71.6 | 20.2 | 8 | Not Applicable |
| Water pH | 7.4 | 7.2 - 7.7 | 0,2 | 8 | Not less than 6.0 or greater than 8.5 units |
| Apparent Color (PCU) | 88 | 54 - 124 | 23 | 8 | Not Applicable |
| Total Hardness (mg/L) | 190 | 177 - 202 | 18 | 2 | Not Applicable |
| Major Ions | | | | | |
| Calcium (mg/L) | 68,6 | 64.7 - 72.4 | 5.4 | 2 | Not Applicable |
| Sodium (mg/L) | 22.4 | 18.1 - 26.7 | 6.1 | 2 | Not Applicable |
| Potassium (mg/L) | 2.9 | 2.2 - 3.7 | 1.1 | 2 | Not Applicable |
| Magnesium (mg/L) | 4.5 | 3.8 - 5.2 | 1.0 | 2 | Not Applicable |
| Total Alkalinity (mg/L) | 170.6 | 139.7 - 190,3 | 16.4 | 8 | Not less than 20 mg/L |
| Sulfate (mg/L) | 11.3 | 5.8 - 16.7 | 7.7 | 2 | Not Applicable |
| Chloride (mg/L) | 29.9 | 17.8 - 44.3 | 9.6 | 8 | Not greater than 10% of background |
| Nutrients | | | | | |
| Ammonium (mg/L) | 0.068 | < 0.009 - 0.108 | 0.038 | 8 | Not Applicable |
| Nitrate+nitrite (mg/L) | 0.021 | <0.004 - 0.041 | 0.015 | 8 | Not Applicable |
| Total Nitrogen (mg/L) | 1.41 | 1.08 - 1.61 | 0.16 | 8 | Not Applicable |
| Orthophosphate (mg/L) | 0.028 | 0.005 - 0.066 | 0.019 | 8 | Not Applicable |
| Total Phosphorus (mg/L) | 0.055 | 0.030 - 0.077 | 0.016 | 8 | Not Applicable |
| Silica (mg/L) | 10.0 | 9.4 - 10.5 | 8,0 | 2 | Not Applicable |
| Trace Elements | | | | | |
| Arsenic (µg/L) | <1.5 | <1.5 - <1.5 | | 1 | Less than or equal to 50 µg/L |
| Cadmium (µg/L) | <0.3 | <0.3 - <0.3 | | 1 | Less than or equal to calculated valuusing: e ^{(0.7662} (NH-0.49) |
| Copper (µg/L) | <1.2 | <1.2 - <1.2 | | 1 | Less than or equal to calculated valuusing: e ^{(0.6545](44)-1.465)} |
| iron (µg/L) | 258 | 213 - 302 | 63 | 2 | Less than or equal to 1,000 µg/L |
| Lead (µg/L) | <0.8 | <0.8 - <0.8 | | 1 | Less than or equal to calculated valuesing: e ^{(1,273} (ml)4.705) |
| Zinc (µg/L) | 8 | 8 - 8 | 1 | 1 | Less than or equal to calculated valuusing: e ^(0.0473[hit]-0.7614) |

Table 8. Summary of Water Quality Parameters Collected by Grab Sampling at Station WWEIR for the Period from May 1998 through October 1998.

| Parameters | Mean | Range | Standard Deviation | Number of Samples | Criteria for Class III Predominantly Fresh Surface Waters, FAC 62-302 |
|------------------------------------|-------|---------------|-----------------------|----------------------|---|
| Physical | | | | | |
| Water Temperature (°C) | 29.1 | 25.2 - 33.2 | 2.4 | 12 | Not Applicable |
| Specific Conductance (µmhos/cm) | 632 | 459 - 738 | 77 | 12 | Not greater than 50% above background or 1,275 µmhos/cm |
| Total Suspended Solids (mg/L) | | * | | -0 | Not Applicable |
| Turbidity (NTU) | | - | | 0 | Less than or equal to 29 NTU above background |
| Dissolved Oxygen (mg/L) | 2.8 | 1.2 - 4.2 | 1.1 | 12 | Not be less than 5.0 mg/L |
| Dissolved Oxygen (% Saturation) | 34.8 | 14.6 - 55.3 | 14.0 | 12 | Not Applicable |
| Water pH | 7.2 | 6.6 - 7.7 | 0.4 | 12 | Not less than 6.0 or greater than 8.5 units |
| Apparent Color (PCU) | | - | | 0 | Not Applicable |
| Total Hardness (mg/L) | | - | | 0 | Not Applicable |
| Major lons | | | • | | |
| Calcium (mg/L) | | • | | 0 | Not Applicable |
| Sodium (mg/L) | | • | | 0 | Not Applicable |
| Potassium (mg/L) | | - | | 0 | Not Applicable . |
| Magnesium (mg/L) | | - | | 0 | Not Applicable |
| Total Alkalinity (mg/L) | | - | | 0 | Not less than 20 mg/L |
| Sulfate (mg/L) | | - | | 0 | Not Applicable |
| Chloride (mg/L) | | - | | 0 | Not greater than 10% of background |
| Nutrients | | | | | |
| Ammonum (mg N/L) | | - | | 0 | Not Applicable |
| Nitrate+nitrite (mg N/L) | | - | | . 0 | Not Applicable |
| Total Nitrogen (mg/L) | 1.94 | 1.94 - 1.94 | | 1 | Not Applicable |
| Orthophosphate (mg/L) | | - | | 0 | Not Applicable |
| Total Phosphorus (mg/L) | 0.045 | 0.015 - 0.088 | 0.020 | 26 | Not Applicable |
| Silica (mg/L) | | • | ٠ | 0 | Not Applicable |
| Trace Elements | | | | | •• |
| Arsenic (μg/L) | | • | - | 0 | Less than or equal to 50 µg/L |
| Cadmium (μg/L) | | - | | 0 | Less than or equal to calculated valusing: e ^{(0.7862} (hH-0.49) |
| Copper (μg/L) | | • | | 0 | Less than or equal to calculated valuesing: e ^(0.8545[H4]-1.405) |
| lron (μg/L) | | • | | 0 | Less than or equal to 1,000 µg/L |
| Lead (μg/L) | | - | | 0 | Less than or equal to calculated valuating: e ^(1273[ref] 4,705) |
| Zinc (μg/L) | | - | | 0 | Less than or equal to calculated valuating: e ^{(0.8470[h+]-0.7814}) |

Table 9. Summary of Water Quality Parameters Collected by Grab Sampling at Station NFEED for the Period from May 1998 through October 1998.

| Parameters | Mean | Range | Standard Deviation | Number of Samples | Criteria for Class III Predominantly Fresh Surface Waters, FAC 62-302 |
|------------------------------------|-------|---------------|-----------------------|----------------------|---|
| Physical | | | | | |
| Water Temperature (°C) | 30.0 | 25.6 - 32.7 | 1.7 | 26 | Not Applicable |
| Specific Conductance (µmhos/cm) | 473 | 424 - 517 | 26 | 26 | Not greater than 50% above background or 1,275 µmhos/cm |
| Total Suspended Solids (mg/L) | | - | | 0 | Not Applicable |
| Turbidity (NTU) | | - | | 0 | Less than or equal to 29 N I U above background |
| Dissolved Oxygen (mg/L) | 4.6 | 1,0 - 8,4 | 1,8 | 26 | Not be less than 5.0 mg/L |
| Dissolved Oxygen (% Saturation) | 58.7 | 13.1 - 111.0 | 23.8 | 26 | Not Applicable |
| Water pH | 7.4 | 6.5 - 7.9 | 0.3 | 26 | Not less than 6.0 or greater than 8.5 units |
| Apparent Color (PCU) | | - | | 0 | Not Applicable |
| Total Hardness (mg/L) | | • | | 0 | Not Applicable |
| Major ions | | | | | |
| Calcium (mg/L) | | - | | 0 | Not Applicable |
| Sodium (mg/L) | | - | Ì | 0 | Not Applicable |
| Potassium (mg/L) | | | | 0 | Not Applicable |
| Magnesium (mg/L) | | - | | 0 | Not Applicable |
| Total Alkalinity (mg/L) | | • | | 0 | Not less than 20 mg/L |
| Sulfate (mg/L) | | - | | 0 | Not Applicable |
| Chloride (mg/L) | | • | | 0 | Not greater than 10% of background |
| Nutrients | | | | • | |
| Ammonium (mg/L) | | | | 0 | Not Applicable |
| Nitrate+nitrite (mg/L) | | - | | 0 | Not Applicable |
| Total Nitrogen (mg/L) | | - | | 0 | Not Applicable |
| Orthophosphate (mg/L) | | • | | 0 | Not Applicable |
| Total Phosphorus (mg/L) | 0.083 | 0.031 - 0.194 | 0.051 | 26 | Not Applicable |
| Silica (mg/L) | | • | | 0 | Not Applicable |
| Trace Elements | | | | | |
| Arsenic (μg/L) | | - | | 0 | Less than or equal to 50 µg/L |
| Cadmium (µg/L) | | * | | 0 | Less than or equal to calculated valuating: e ^(0,7882[hH]-9,49) |
| Copper (µg/L) | | • | | 0 | Less than or equal to calculated valuating: e(0.05545[H]-1.465) |
| iron (µg/L) | | - | | 0 | Less than or equal to 1,000 µg/L |
| Lead (µg/L) | | - | | 0 | Less than or equal to calculated valuating: e ^{(1273(nH) 4,705)} |
| Zinc (µg/L) | | - | | 0 | Less than or equal to calculated valuusing: e ^{(0.9473} (HH)-0.7614) |

Table 10. Summary of Water Quality Parameters Collected by Grab Sampling at Station S190 for the Period from May 1998 through October 1998.


| Parameters | Mean | Rånge | Standard Deviation | Number of Samples | Criteria for Class III Predominantly Fresh Surface Waters, FAC 62-302 |
|------------------------------------|-------|----------------|-----------------------|----------------------|--|
| Physical | | | | | |
| Water Temperature (°C) | 30.4 | 28.9 - 32.9 | 1.4 | 7 | Not Applicable |
| Specific Conductance (µmhos/cm) | 561 | 498 - 615 | 40 | 7 | Not greater than 50% above background or 1,275 µmhos/cm |
| Total Suspended Solids (mg/L) | 3.0 | 3 - 3 | 0.0 | 2 | Not Applicable |
| Turbidity (NTU) | 5.8 | 1.0 - 30.4 | 10.8 | 7 | Less than or equal to 29 NTU above background |
| Dissolved Oxygen (mg/L) | 4.2 | 2.7 - 6.9 | 1.5 | 7 | Not be less than 5.0 mg/L |
| Dissolved Oxygen (% Saturation) | 53.9 | 35.1 - 88.2 | 18,9 | 7 | Not Applicable |
| Water pH | 7.4 | 6.9 - 7.6 | 0.2 | 7 | Not less than 6.0 or greater than 8.5 units |
| Apparent Color (PCU) | 71 | 42 - 104 | 23 | 7 | Not Applicable |
| Total Hardness (mg/L) | 236 | 230 - 242 | 8 | 2 | Not Applicable |
| Major lons | | - | | | |
| Calcium (mg/L) | 82,9 | 81.7 - 84.1 | 1.7 | 2 | Not Applicable |
| Sodium (mg/L) | 30.3 | 27.3 - 33.2 | 4.2 | 2 | Not Applicable |
| Potassium (mg/L) | 2.8 | 2.5 - 3.1 | 0.4 | 2 | Not Applicable . |
| Magnesium (mg/L) | 7.0 | 6.3 - 7.7 | 1.0 | 2 | Not Applicable |
| Total Alkalinity (mg/L) | 212.6 | 186.0 - 245.6 | 19.7 | 7 | Not less than 20 mg/L |
| Sulfate (mg/L) | 12.0 | 10.0 - 14.0 | 2.8 | 2 | Not Applicable |
| Chloride (mg/L) | 39.7 | 28.9 - 48.8 | 7.6 | 7 | Not greater than 10% of background |
| Nutrients | | | | | |
| Ammonium (mg/L) | 0.013 | <0.009 - 0.036 | 0,010 | 7 | Not Applicable |
| Nitrate+nitrite (mg/L) | 0.048 | 0.005 - 0.226 | 0.081 | 7 | Not Applicable |
| Total Nitrogen (mg/L) | 1,47 | 1.09 - 2.63 | 0.54 | 7 | Not Applicable |
| Orthophosphate (mg/L) | 0.018 | 0.007 - 0.043 | 0,014 | 7 | Not Applicable |
| Total Phosphorus (mg/L) | 0.063 | 0.022 - 0.139 | 0.039 | 7 | Not Applicable |
| Silica (mg/L) | 11.3 | 10.3 - 12.4 | 1.5 | 2 | Not Applicable |
| Trace Elements | | | | | |
| Arsenic (μg/L) | <1.5 | <1.5 - <1.5 | | 1 | Less than or equal to 50 µg/L |
| Cadmium (µg/L) | <0.3 | <0.3 - <0.3 | | 1 | Less than or equal to calculated value using: e ^(0.7652[hH]-3.49) |
| Copper (µg/L) | <1.2 | <1.2 - <1.2 | | 1 | Less than or equal to calculated value using: e ^{(0.0545[ht]} -1,465) |
| iron (μg/L) | 150 | 50 - 249 | 141 | 2 | Less than or equal to 1,000 µg/L |
| Lead (μg/L) | <0.8 | <0.8 - <0.8 | | 1 | Less than or equal to calculated value using: e ^{(1,273} (H)4.705) |
| Zinc (μg/L) | <4 | <4 - <4 | | 1 | Less than or equal to calculated value using: e ^{(0,0473(nH)-0,7614)} |

Table 11. Trace metal concentrations above the method detection limit and compared with Class III Standard calculated using water hardness.

| Station Number | Date Collected | Total C (µg | | Total (µg | Zinc /L) | Total Iron (μg/L) | |
|-------------------|-------------------|----------------|----------|--------------|-------------|----------------------|----------|
| Mumber | Collected | Measured | Standard | Measured | Standard | Measured | Standard |
| L3BRS | 16-Jul-98 | 3.9 | <18.0 | 5.6 | <160 | 882 | <1,000 |
| L3BRS | 08-Oct-98 | | | | | 1,110 | <1,000 |
| S140 | 30-Jul-98 | **** | | 7.7 | <192 | 213 | <1,000 |
| S140 | 08-Oct-98 | | | | | 302 | <1,000 |
| USSO | 16-Jul-98 | | | | | 159 | <1,000 |
| USSO | 08-Oct-98 | | | | **** | 337 | <1,000 |


(Blank Page)

APPENDIX I. Flow Chart for Water Flow and Water Quality Data Collected for the SFWMD/Seminole Cooperative Agreement




Addendum to Appendix I. Flow Chart for Water Flow and Water Quality Data Collected for the Seminole/SFWMD Cooperative Agreement

Updated 3/1/99



APPENDIX II. SFWMD/Seminole Agreement Sampling Station Names



(Blank Page)

APPENDIX III. Total phosphorus concentration data for the period of May 1, 1998 through October 31, 1998.

For L3BRS and USL3BRS:

(1) Grab sample TP concentration.

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|----------|---------|----------|------|-----------|-----------|-----------|--------|
| L3BRS | CAMB | 19980521 | 0 | 0.045 | 60535 | L10152-7 | SFWMD |
| (USL3BRS | CAMB | 19980521 | 0 | 0.061 | 60527 | L10153-7 | SFWMD) |
| L3BRS | CAMB | 19980701 | 0 | 0.132 | 60604 | L10409-7 | SFWMD |
| (USL3BRS | CAMB | 19980709 | 0 | 0.094 | 60634 | L10446-7 | SFWMD) |
| L3BRS | CAMB | 19980716 | 0 | 0.192 | 60653 | L10493-10 | SFWMD |
| L3BRS | CAMB | 19980812 | 0 | 0.204 | 60700 | L10648-10 | SFWMD |
| L3BRS | CAMB | 19980827 | 0 | 0.194 | 60729 | L10759-10 | SFWMD |
| L3BRS | CAMB | 19980909 | 0 | 0.156 | 60753 | L10831-7 | SFWMD |
| L3BRS | CAMB | 19980930 | 0 | 0.166 | 60781 | L10973-7 | SFWMD |
| L3BRS | CAMB | 19981008 | 0 | 0.161 | 60821 | L11020-10 | SFWMD |
| L3BRS | CAMB | 19981022 | 0 | 0.083 | 60839 | L11116-7 | SFWMD |

| Station | Project | Date | Type | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|---------------------|------|-----------|-----------|----------|---------|
| USL3BRS | CAMB | 19980507 | 24 | 0.082 | 60512 | L10061-6 | SFWMD |
| USL3BRS | CAMB | 19980514 | 24 | 0.076 | 60517 | L10106-4 | SFWMD |
| USL3BRS | CAMB | 19980528 | 24 | 0.077 | 60546 | L10200-4 | SFWMD |
| USL3BRS | CAMB | 19980603 | 24 | 0.042 | 60551 | L10238-4 | SFWMD |
| USL3BRS | CAMB | 19980611 | 24 | 0.063 | 60572 | L10287-4 | SFWMD |
| USL3BRS | CAMB | 19980618 | 24 | 0.049 | 60593 | L10333-3 | SFWMD |
| USL3BRS | CAMB | 19980625 | 24 | 0.133 | 60615 | L10378-4 | SFWMD |
| USL3BRS | CAMB | 19980702 | 24 | 0.143 | 60622 | L10414-3 | SFWMD . |
| USL3BRS | CAMB | 19980716 | 24 | 0.085 | 60641 | L10492-6 | SFWMD |
| USL3BRS | CAMB | 19980723 | 24 | 0.142 | 60738 | L10532-6 | SFWMD |
| USL3BRS | CAMB | 19980730 | 24 | 0.173 | 60675 | L10575-6 | SFWMD |
| USL3BRS | CAMB | 19980813 | 24 | 0.208 | 60689 | L10662-6 | SFWMD |
| USL3BRS | CAMB | 19980820 | 24 | 0.181 | 60709 | L10720-5 | SFWMD |
| USL3BRS | CAMB | 19980827 | 24 | 0.213 | 60716 | L10761-4 | SFWMD |
| USL3BRS | CAMB | 19980903 | 24 | 0.154 | 60745 | L10805-6 | SFWMD |
| USL3BRS | CAMB | 19980910 | 24 | 0.152 | 60764 | L10841-4 | SFWMD |
| USL3BRS | CAMB | 19980917 | 24 | 0.113 | 60773 | L10892-6 | SFWMD |
| USL3BRS | CAMB ' | 19980922 | 24 | 0.192 | 60792 | L10921-4 | SFWMD |
| USL3BRS | CAMB | 19981001 | 24 | 0.199 | 60801 | L10980-4 | SFWMD |
| USL3BRS | CAMB | 19981008 | 24 | 0.132 | 60808 | L11021-4 | SFWMD |
| USL3BRS | CAMB | 19981015 | 24 | 0.176 | 60831 | L11071-6 | SFWMD |
| USL3BRS | CAMB | 19981022 | 24 | 0.122 | 60850 | L11118-4 | SFWMD |
| USL3BRS | CAMB | 19981028 | 24 | 0.090 | 60859 | L11155-6 | SFWMD |
| USL3BRS | CAMB | 19981104 | 24 | 0.078 | 60881 | L11194-6 | SFWMD |

For USSO:

(1) Grab sample TP concentration.

| USSO | CAMB | 19980521 | 0 | 0.063 | 60536 | L10152-8 | SFWMD |
|------|------|----------|---|--------|-------|-----------|-------|
| | | | | | | | |
| USSO | CAMB | 19980603 | 0 | 0.049 | 60553 | L10238-6 | SFWMD |
| USSO | CAMB | 19980603 | 0 | 0.053 | 60559 | L10234-5 | SFWMD |
| USSO | CAMB | 19980611 | 0 | 0.089 | 60576 | L10287-8 | SFWMD |
| USSO | CAMB | 19980618 | 0 | 0.033 | 60591 | L10333~1 | SFWMD |
| USSO | CAMB | 19980625 | 0 | 0.788* | 60616 | L10378-5 | SFWMD |
| USSO | CAMB | 19980701 | 0 | 0.227 | 60605 | L10409-8 | SFWMD |
| USSO | CAMB | 19980702 | 0 | 0.193 | 60621 | L10414-2 | SFWMD |
| USSO | CAMB | 19980716 | 0 | 0.077 | 60654 | L10493-11 | SFWMD |
| USSO | CAMB | 19980805 | 0 | 0.059 | 60683 | L10611-7 | SFWMD |
| USSO | CAMB | 19980812 | 0 | 0.145 | 60701 | L10648-11 | SFWMD |
| USSO | CAMB | 19980827 | 0 | 0.120 | 60730 | L10759-11 | SFWMD |
| USSO | CAMB | 19980909 | 0 | 0.090 | 60754 | L10831-8 | SFWMD |
| USSO | CAMB | 19980930 | 0 | 0.089 | 60782 | L10973-8 | SFWMD |
| USSO | CAMB | 19981008 | 0 | 0.174 | 60822 | L11020-11 | SFWMD |
| USSO | CAMB | 19981022 | 0 | 0.075 | 60843 | L11116-11 | SFWMD |
| | | | | | | | |

^{*} denotes a sample deemed to be an outlier and not included in the statistics or load calculation.

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|-----------|-----------|----------|--------|
| USSO | CAMB | 19980507 | 24 | 0.078 | 60513 | L10061-7 | SFWMD |
| USSO | CAMB | 19980514 | 24 | 0.060 | 60518 | L10106-5 | SFWMD |
| USSO | CAMB | 19980521 | 24 | 0.047 | 60528 | L10153-8 | SFWMD |
| USSO | CAMB | 19980702 | 24 | 0.343 | 60620 | L10414-1 | SFWMD |
| USSO | CAMB | 19980709 | 24 | 0.243 | 60635 | L10446-8 | SFWMD |
| _USSO | CAMB | 19980716 | 24 | 0.078 | 60642 | L10492-7 | SFWMD |
| USSO | CAMB | 19980723 | 24 | 0.087 | 60739 | L10532-7 | SFWMD |
| USSO | CAMB | 19980730 | 24 | 0.079 | 60676 | L10575-7 | SFWMD |
| USSO | CAMB | 19980813 | 24 | 0.095 | 60690 | L10662-7 | SFWMD |
| USSO | CAMB | 19980820 | 24 | 0.112 | 60712 | L10720-8 | SFWMD |
| USSO | CAMB | 19980827 | 24 | 0.102 | 60713 | L10761-1 | SFWMD |
| USSO | CAMB | 19980903 | 24 | 0.105 | 60746 | L10805-7 | SFWMD |
| USSO | CAMB | 19980917 | 24 | 0.122 | 60774 | L10892-7 | SFWMD |
| USSO | CAMB | 19980922 | 24 | 0.094 | 60789 | L10921-1 | SFWMD |
| USSO | CAMB | 19981008 | 24 | 0.153 | 60805 | L11021-1 | SFWMD |
| USSO | CAMB | 19981015 | 24 | 0.140 | 60830 | L11071-5 | SFWMD |
| USSO | CAMB | 19981028 | 24 | 0.081 | 60856 | L11155-3 | SFWMD |
| USSO | CAMB | 19981104 | 24 | 0.082 | 60882 | L11194-7 | SFWMD |

For S140:

Grab sample TP concentration.

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|-----------|-----------|-----------|--------|
| S140 | CAMB | 19980521 | 0 | 0.052 | 60542 | L10152-14 | SFWMD |
| S140 | CAMB | 19980701 | 0 | 0.054 | 60610 | L10409-13 | SFWMD |
| S140 | CAMB | 19980730 | 0 | 0.068 | 60669 | L10570-4 | SFWMD |
| S140 | CAMB | 19980827 | 0 | 0.077 | 60733 | L10759-14 | SFWMD |
| S140 | CAMB | 19980909 | 0 | 0.068 | 60760 | L10831-14 | SFWMD |
| S140 | CAMB | 19980930 | 0 | 0.036 | 60785 | L10973-11 | SFWMD |
| S140 | CAMB | 19981008 | 0 | 0.051 | 60825 | L11020-14 | SFWMD |
| S140 | CAMB | 19981022 | 0 | 0.030 | 60846 | L11116-14 | SFWMD |

For WEIR:

(1) Grab sample TP concentration.

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|-----------|-----------|----------|--------|
| WWEIR | SEMI | 19980507 | 0 | 0.044 | 1423 | L10062-5 | SFWMD |
| WWEIR | SEMI | 19980514 | 0 | 0.034 | 1429 | L10107-5 | SFWMD |
| WWEIR | SEMI | 19980521 | 0 | 0.055 | 1437 | L10154-7 | SFWMD |
| WWEIR | SEMI | 19980528 | 0 | 0.073 | 1446 | L10201-8 | SFWMD |
| WWEIR | SEMI | 19980603 | 0 | 0.044 | 1453 | L10239-7 | SFWMD |
| WWEIR | SEMI | 19980611 | 0 | 0.039 | 1459 | L10288-5 | SFWMD |
| WWEIR | SEMI | 19980618 | 0 | 0.050 | 1464 | L10334-4 | SFWMD |
| WWEIR | SEMI | 19980625 | 0 | 0.055 | 1473 | L10379-6 | SFWMD |
| WWEIR | SEMI | 19980702 | 0 | 0.052 | 1477 | L10415-4 | SFWMD |
| WWEIR | SEMI | 19980709 | 0 | 0.052 | 1485 | L10447-5 | SFWMD |
| WWEIR | SEMI | 19980716 | 0 | 0.047 | 1491 | L10491-5 | SFWMD |
| WWEIR | SEMI | 19980723 | 0 | 0.020 | 1497 | L10533-5 | SFWMD |
| WWEIR | SEMI | 19980730 | 0 | 0.020 | 1503 | L10576-5 | SFWMD |
| WWEIR | SEMI | 19980805 | 0 | 0.016 | 1509 | L10613-5 | SFWMD |
| WWEIR | SEMI | 19980813 | . 0 | 0.015 | 1515 | L10663-5 | SFWMD |
| WWEIR | SEMI | 19980820 | 0 | 0.028 | 1521 | L10721-5 | SFWMD |
| WWEIR | SEMI | 19980827 | 0 | 0.050 | 1526 | L10760-4 | SFWMD |
| WWEIR | SEMI | 19980903 | 0 | 0.044 | 1532 | L10806-3 | SFWMD |
| WWEIR | SEMI | 19980910 | 0 | 0.028 | 1537 | L10842-4 | SFWMD |
| WWEIR | SEMI | 19980917 | 0 | 0.022 | 1541 | L10891-4 | SFWMD |
| WWEIR | SEMI | 19980922 | 0 | 0.085 | 1543 | L10920-2 | SFWMD |
| WWEIR | SEMI | 19981001 | 0 | 0.088 | 1550 | L10981-4 | SFWMD |
| WWEIR | SEMI | 19981008 | 0 | 0.062 | 1555 | L11022-5 | SFWMD |
| WWEIR | SEMI | 19981015 | 0 | 0.071 | 1557 | L11070-2 | SFWMD |
| WWEIR | SEMI | 19981022 | 0 | 0.050 | 1561 | L11117-2 | SFWMD |
| WWEIR | SEMI | 19981028 | 0 | 0.034 | 1565 | L11156-2 | SFWMD |

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|-----------|-----------|----------|--------|
| WWEIR | SEMI | 19980723 | 24 | 0.033 | 1498 | L10533-6 | SFWMD |
| WWEIR | SEMI | 19980730 | 24 | 0.040 | 1504 | L10576-6 | SFWMD |
| WWEIR | SEMI | 19980820 | 24 | 0.019 | 1522 | L10721-6 | SFWMD |
| WWEIR | SEMI | 19980827 | 24 | 0.040 | 1527 | L10760-5 | SFWMD |
| WWEIR | SEMI | 19980903 | 24 | 0.043 | 1533 | L10806-4 | SFWMD |
| WWEIR | SEMI | 19980910 | 24 | 0.050 | 1536 | L10842-3 | SFWMD |
| WWEIR | SEMI | 19980917 | 24 | 0.030 | 1540 | L10891-3 | SFWMD |
| WWEIR | SEMI | 19980922 | 24 | 0.052 | 1544 | L10920-3 | SFWMD |
| WWEIR | SEMI | 19981001 | 24 | 0.098 | 1549 | L10981-3 | SFWMD |
| WWEIR | SEMI | 19981008 | 24 | 0.078 | 1554 | L11022-4 | SFWMD |
| WWEIR | SEMI | 19981015 | 24 | 0.058 | 1556 | L11070-1 | SFWMD |
| WWEIR | SEMI | 19981022 | 24 | 0.041 | 1560 | L11117-1 | SFWMD |
| WWEIR | SEMI | 19981028 | 24 | 0.042 | 1564 | L11156-1 | SFWMD |
| WWEIR | SEMI | 19981104 | 24 | 0.042 | 1570 | L11195-3 | SFWMD |

For NFEED:

(1) Grab sample TP concentration.

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|-----------|--------------|----------|--------|
| NFEED | SEMI | 19980507 | 0 | 0.054 | 1420 | L10062-2 | SFWMD |
| NFEED | SEMI | 19980514 | 0 | 0.067 | 1426 | L10107-2 | SFWMD |
| NFEED | SEMI | 19980521 | 0 | 0.051 | 1434 | L10154-4 | SFWMD |
| NFEED | SEMI | 19980528 | 0 | 0.064 | 1442 | L10201-4 | SFWMD |
| NFEED | SEMI | 19980603 | 0 | 0.041 | 1450 | L10239-4 | SFWMD |
| NFEED | SEMI | 19980611 | 0 | 0.031 | 1456 | L10288-2 | SFWMD |
| NFEED | SEMI | 19980618 | 0 | 0.044 | 1467 | L10334-7 | SFWMD |
| NFEED | SEMI | 19980625 | 0 | 0.043 | 1469 | L10379-2 | SFWMD |
| NFEED | SEMI | 19980702 | 0 | 0.044 | 1480 | L10415-7 | SFWMD |
| NFEED | SEMI | 19980709 | 0 | 0.043 | 1482 | L10447-2 | SFWMD |
| NFEED | SEMI | 19980716 | 0 | 0.042 | 1488 | L10491-2 | SFWMD |
| NFEED | SEMI | 19980723 | 0 | 0.057 | 1494 | L10533-2 | SFWMD |
| NFEED | SEMI | 19980730 | 0 | 0.050 | 1500 | L10576-2 | SFWMD |
| NFEED | SEMI | 19980805 | 0 | 0.042 | 1506 | L10613-2 | SFWMD |
| NFEED | SEMI | 19980813 | 0 | 0.035 | 1511 | L10663-1 | SFWMD |
| NFEED | SEMI | 19980820 | 0 | 0.046 | 1518 | L10721-2 | SFWMD |
| NFEED | SEMI | 19980827 | 0 | 0.194 | 1529 | L10760-7 | SFWMD |
| NFEED | SEMI | 19980903 | 0 | 0.159 | 153 1 | L10806-2 | SFWMD |
| NFEED | SEMI | 19980910 | 0 | 0.149 | 1535 | L10842-2 | SFWMD |
| NFEED | SEMI | 19980917 | 0 | 0.112 | 1539 | L10891-2 | SFWMD |
| NFEED | SEMI | 19980922 | 0 | 0.102 | 1545 | L10920-4 | SFWMD |
| NFEED | SEMI | 19981001 | 0 | 0.129 | 1548 | L10981-2 | SFWMD |
| NFEED | SEMI | 19981008 | 0 | 0.163 | 1553 | L11022-3 | SFWMD |
| NFEED | SEMI | 19981015 | 0 | 0.163 | 1559 | L11070-4 | SFWMD |
| NFEED | SEMI | 19981022 | 0 | 0.139 | 1563 | L11117-4 | SFWMD |
| NFEED | SEMI | 19981028 | 0 | 0.095 | 1567 | L11156-4 | SFWMD |

For NFEED:

| Station | Project | Date | Туре | TP (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|-----------|-----------|----------|--------|
| NFEED | SEMI | 19980507 | 24 | 0.068 | 1419 | L10062-1 | SFWMD |
| NFEED | SEMI | 19980514 | 24 | 0.056 | 1425 | L10107-1 | SFWMD |
| NFEED | SEMI | 19980521 | 24 | 0.062 | 1431 | L10154-1 | SFWMD |
| NFEED | SEMI | 19980528 | 24 | 0.033 | 1439 | L10201-1 | SFWMD |
| NFEED | SEMI | 19980603 | 24 | 0.050 | 1447 | L10239-1 | SFWMD |
| NFEED | SEMI | 19980611 | 24 | 0.038 | 1455 | L10288-1 | SFWMD |
| NFEED | SEMI | 19980618 | 24 | 0.041 | 1466 | L10334-6 | SFWMD |
| NFEED | SEMI | 19980625 | 24 | 0.051 | 1468 | L10379-1 | SFWMD |
| NFEED | SEMI | 19980702 | 24 | 0.060 | 1479 | L10415-6 | SFWMD |
| NFEED | SEMI | 19980709 | 24 | 0.067 | 1481 | L10447-1 | SFWMD |
| NFEED | SEMI | 19980716 | 24 | 0.061 | 1487 | L10491-1 | SFWMD |
| NFEED | SEMI | 19980723 | 24 | 0.067 | 1493 | L10533-1 | SFWMD |
| NFEED | SEMI | 19980730 | 24 | 0.056 | 1499 | L10576-1 | SFWMD |
| NFEED | SEMI | 19980805 | 24 | 0.055 | 1505 | L10613-1 | SFWMD |
| NFEED | SEMI | 19980813 | 24 | 0.045 | 1512 | L10663-2 | SFWMD |
| NFEED | SEMI | 19980820 | 24 | 0.052 | 1517 | L10721-1 | SFWMD |
| NFEED | SEMI | 19980827 | 24 | 0.187 | 1528 | L10760-6 | SFWMD |
| NFEED | SEMI | 19980903 | 24 | 0.166 | 1530 | L10806-1 | SFWMD |
| NFEED | SEMI | 19980910 | 24 | 0.153 | 1534 | L10842-1 | SFWMD |
| NFEED | SEMI | 19980917 | 24 | 0.127 | 1538 | L10891-1 | SFWMD |
| NFEED | SEMI | 19980922 | 24 | 0.117 | 1546 | L10920-5 | SFWMD |
| NFEED | SEMI | 19981001 | 24 | 0.133 | 1547 | L10981-1 | SFWMD |
| NFEED | SEMI | 19981008 | 24 | 0.116 | 1552 | L11022-2 | SFWMD |
| NFEED | SEMI | 19981015 | 24 | 0.143 | 1558 | L11070-3 | SFWMD |
| NFEED | SEMI | 19981022 | 24 | 0.143 | 1562 | L11117-3 | SFWMD |
| NFEED | SEMI | 19981028 | 24 | 0.104 | 1566 | L11156-3 | SFWMD |
| NFEED | SEMI | 19981104 | 24 | 0.091 | 1568 | L11195-1 | SFWMD |

For S190:

Grab sample TP concentration.

| Station | Project | Date | Туре | TP | (mg/L) | Sample_ID | LIMS no. | Source |
|---------|---------|----------|------|----|--------|-----------|-----------|--------|
| S190 | CAMB | 19980521 | 0 | 0. | .139 | 60537 | L10152-9 | SFWMD |
| S190 | CAMB | 19980701 | 0 | 0. | 030 | 60609 | L10409-12 | SFWMD |
| S190 | CAMB | 19980730 | 0 | 0. | 022 | 60666 | L10570-1 | SFWMD |
| S190 | CAMB | 19980827 | 0 | 0. | 062 | 60731 | L10759-12 | SFWMD |
| S190 | CAMB | 19980909 | 0 | 0. | 047 | 60755 | L10831-9 | SFWMD |
| S190 | CAMB | 19980930 | 0 | 0. | 056 | 60783 | L10973-9 | SFWMD |
| S190 | CAMB | 19981008 | 0 | 0. | 085 | 60823 | L11020-12 | SFWMD |

Addendum

- L28IS Nutrient, Water Quality and Flow Data Summary for the Period of March 1, 1998 through September 30, 1998
- Figure A1. L28IS TP Load, Flow and TP Concentration for the Period of March 1, 1998 through September 30, 1998
- Table A1. L28IS Total Phosphorus (TP) Concentration and Water Flow Data Summary for the Period of March 1, 1998 through September 30, 1998
- Table A2. L28IS Monthly Total Phosphorus (TP) Load and Flow Summary for the Period of March 1998 through September 1998
- Table A3. L28IS TP Concentration Data for the Period of March 1998 through September 1998
- Table A4. Water Quality Data for Grab Samples Collected at Station L28IS from March 1998 through September 1998
- Table A5. Water Quality Data Collected Using Auto-Samplers at Station L28IS from March 1998 through September 1998




Table A1. Seminole/SFWMD Agreement total phosphorus (TP) data and water flow data summary for the period of March 1, 1998 through September 30, 1998.

For L28IS:

```
term
        clab
                glab
                          glab
                                  dbkey qsign itype ldsign iymdcomp
L28IS
        L28IS
                L28I@175
                          L28IS_O FF812 1
                                              1
 Grab sample n = 10
    first datum :
                    1998/06/26
    last datum :
                    1998/09/18
    average value (arithmetic mean) = 30.8 ppb
    range = 17 to 64ppb
 Grab sample w/ + flow = 7
    first datum :
                    1998/06/26
    last datum :
                    1998/09/18
    average value (arithmetic mean) = 34.4 ppb
    range = 17 to 64 ppb
    flow weighted mean for data w/ +flow = 31.8 ppb
    regression: TP conc (ppb) = 37.9384 - 0.0379 * flow (cfs)
    load ratio of comp:grab = 1.54347 (common days = 7)
 Autosampler (flow proportional composite) n = 25
    first datum :
                    1998/03/13
    last datum :
                    1998/09/18
    average value (arithmetic mean) = 53.3 ppb
    range = 1 to 95 ppb
    flow weighted mean for data = 43.6 ppb
    regression: TP conc (ppb) = 62.1999 - 0.1849 * flow (cfs)
    note: composite sample missing after 1998/07/17 for 14 days
Flow data from 1998/03/01 to 1998/09/30
    number of no flow days = 0
    number of positive flow days = 131
    total positive flow = 12883.279 cfs-d
    number of negative flow days = 83
    total negative flow = 3424.500 cfs-d
    no missing flow data
```

Table A2. L28IS total phosphorus (TP) load calculation monthly summary for the period of March 1, 1998 through September 30, 1998.

Note: Flow is in million cubic meters and in (thousand acre-feet).

Flow-weighted mean concentration for each month is calculated by dividing monthly load with monthly total flow.

For L28IS:

| Station | month d | lays | flow | load(Kg) | fwmc(ppb) | flow_negative load_neg. |
|---------|---------|------|-----------------|----------|-----------|---------------------------|
| L28IS | 1998/03 | 31 | 10.166 (8.242) | 432.579 | 42.552 | -0.044 (-0.036) -1.982 |
| L28IS | 1998/04 | 30 | 1.337 (1.084) | 85.360 | 63.865 | -1.555 (-1.261)-118.803 |
| L28IS | 1998/05 | 31 | 2.486 (2.016) | 52.477 | 21.107 | -1.957 (-1.586) -95.706 |
| L28IS | 1998/06 | 30 | 2.068 (1.677) | 94.438 | 45.667 | -1.862 (-1.509) -105.332 |
| L28IS | 1998/07 | 31 | 1.127 (0.914) | 63.164 | 56.037 | -2.040 (-1.654)-118.965 |
| L28IS | 1998/08 | 31 | 6.460 (5.238) | 268.659 | 41.585 | -0.548 (-0.444) -28.658 |
| L28IS | 1998/09 | 30 | 7.876 (6.385) | 626.751 | 79.582 | -0.373 (-0.302) -26.000 |

Table A3. Total phosphorus concentration data for the period of March 1, 1998 through September 30, 1998.

For L28IS:

L28IS

MICC

19980918

| (1) Grab | sample T | P concentration | | | | |
|----------|----------|-----------------|-------|-----------|--------------|----------------|
| Station | _ | | | TP (mg/L) | Sample_ID | Source |
| L28IS | MICC | 19980626 | 0 | 0.024 | 00047 | SERP, FIU MICC |
| L28IS | MICC | 19980703 | 0 | 0.034 | 00050 | SERP, FIU MICC |
| L28IS | MICC | 19980710 | 0 | 0.058 | 00053 | SERP, FIU MICC |
| L28IS | MICC | 19980717 | 0 | 0.021 | 00056 | SERP, FIU MICC |
| L28IS | MICC | 19980807 | 0 | 0.026 | 00059 | SERP, FIU MICC |
| L28IS | MICC | 19980814 | 0 | 0.017 | 00062 | SERP, FIU MICC |
| L28IS | MICC | 19980821 | 0 | 0.017 | 00065 | SERP, FIU MICC |
| L28IS | MICC | 19980904 | 0 | 0.020 | 00068 | SERP, FIU MICC |
| L28IS | MICC | 19980911 | 0 | 0.027 | 00071 | SERP, FIU MICC |
| L28IS | MICC | 19980918 | 0 | 0.064 | 00074 | SERP, FIU MICC |
| | | | | | | |
| | | low-Proportion: | | | ncentration. | |
| Station | Project | Date Sample | _type | TP (mg/L) | Sample_ID | Source |
| L28IS | MICC | 19980313 | 24 | 0.043 | 00003 | SERP, FIU MICC |
| L28IS | | 19980320 | 24 | 0.041 | 00006 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.043 | 00009 | SERP, FIU MICC |
| L28IS | MICC | 19980403 | 24 | 0.045 | 00012 | SERP, FIU MICC |
| L28IS | MICC | 19980410 | 24 | 0.051 | 00015 | SERP, FIU MICC |
| L28IS | MICC | 19980417 | 24 | 0.072 | 00018 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.095 | 00021 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.052 | 00024 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.052 | 00027 | SERP, FIU MICC |
| L28IS | MICC | 19980515 | 24 | 0.001 | 00030 | SERP, FIU MICC |
| L28IS | MICC | 19980522 | 24 | 0.030 | 00033 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.066 | 00036 | SERP, FIU MICC |
| L28IS | MICC | 19980605 | 24 | 0.028 | 00039 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.048 | 00042 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.069 | 00045 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.073 | 00048 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.058 | 00051 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.061 | 00054 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.047 | 00057 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.069 | 00060 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.046 | 00063 | SERP, FIU MICC |
| L28IS | MICC | 19980821 | | 0.026 | 00066 | SERP, FIU MICC |
| L28IS | MICC | | 24 | 0.072 | 00069 | SERP, FIU MICC |
| L28IS | MICC | 19980911 | 24 | 0.064 | 00072 | SERP, FIU MICC |
| T.28TC | MTCC | 10000010 | 2.4 | 0 001 | 00075 | CODD DITT MICO |

0.081

00075

SERP, FIU MICC

24

Table A4. Water Quality Data for Grab Samples Collected at Station L28IS from March 1998 through September 1998.

| No. of Observations | Maximum | Minimum | Median | Standard Deviation | Mean | 09/18/1998 | 09/11/1998 | 09/04/1998 | 08/21/1998 | 08/14/1998 | 08/07/1998 | 07/17/1998 | 07/10/1998 | 07/03/1998 | 06/26/1998 | 06/19/1998 | 06/12/1998 | 06/05/1998 | 05/29/1998 | 05/22/1998 | 05/15/1998 | 05/08/1998 | 05/01/1998 | 04/28/1998 | 04/17/1998 | 04/10/1998 | 04/03/1998 | 03/27/1998 | 03/20/1998 | 03/13/1998 | Date Sampled |
|---------------------|---------|---------|--------|--------------------|-------|------------|------------|------------|------------|------------|------------|--|------------|--|--|--|--|------------|------------|------------|------------|------------|--|------------|------------|--|--|------------|---|------------|---|
| 25 | 33.3 | 24.9 | 30.9 | 2.3 | 30.3 | 28.5 | 30.4 | 32.2 | 30.3 | 31.6 | 31.7 | 32.5 | 32.9 | 29.6 | 31.4 | 33.3 | 32,4 | 32.8 | 31.8 | 31.4 | 30.9 | 29.1 | 27.0 | 24.9 | 32.4 | 28.1 | 27.7 | 27.4 | 28.6 | 27.6 | Water Temperature (°C) |
| 25 | 598 | 457 | 576 | 38 | 561 | 528 | 569 | 580 | 533 | 584 | 457 | 460 | 525 | 542 | 564 | 598 | 587 | 589 | 582 | 576 | 562 | 586 | 589 | 555 | 596 | 576 | 590 | 563 | 542 | 594 | Specific Conductance (µmhos/cm) |
| 25 | 7.8 | 6.8 | 7.4 | 0.2 | 7.3 | 7.4 | 7.1 | 7.8 | 7.2 | 7.4 | 7.2 | 7.3 | 7.5 | 7.4 | 7.4 | 7.5 | 7.3 | 7.1 | 7.6 | 7.4 | 6.9 | 7.1 | 7.8 | 7.2 | 7.4 | 6.8 | 7.3 | 7.5 | 7.4 | 7.2 | PΗ |
| 24 | 0.245 | 0.003 | 0.042 | 0.052 | 0.050 | 0.073 | 0.041 | 0.128 | 0.079 | 0.075 | 0.028 | 0.051 | 0.245 | 0.084 | 0.026 | 0.046 | 0.024 | 0.017 | 0.055 | 0.061 | 0.042 | 0.038 | 0.008 | 0.003 | 0.007 | 0.004 | 0.010 | | 0.045 | 0.006 | Dissolved Ammonia (mg N/L) |
| 25 | 0.007 | 0.001 | 0.002 | 0.002 | 0.003 | 0.003 | 0.003 | 0.002 | 0.003 | 0.003 | 0.003 | 0.002 | 0.003 | 0.007 | 0.002 | 0.003 | 0.002 | 0.002 | 0.002 | 0.005 | 0.007 | 0.002 | 0.001 | 0.001 | 0.001 | 0.002 | 0.002 | 0.001 | 0.002 | 0.001 | Dissolved Nitrite (mg N/L) |
| 13 | 0.012 | 0.001 | 0.006 | 0.004 | 0.006 | 0.004 | 0.008 | 0.012 | 0.010 | 0.001 | 0.011 | TO 1 Out Out Of the section of the s | 0.006 | Andrew A. Amazon, Andrews and L. P. Comments | The state of the s | 0.006 | | | 0.002 | 0.007 | 0.005 | | The state of the s | | | 0.001 | | | 0.011 | | Dissolved Nitrate (mg N/L) |
| 10 | 1.572 | 0.836 | 1.074 | 0.191 | 1.102 | 1.091 | 0.836 | 1.057 | 0.997 | 1.031 | 1.019 | 1.213 | 1.572 | 1.101 | 1.099 | | | | | , | | | | | | **** | | | en nytte i seets signe eyigi yn yn goddyson yng | | Total Nitrogen (mg/L) |
| 23 | 0.014 | 0.001 | 0.003 | 0.004 | 0.005 | 0.014 | 0.014 | 0.008 | 0.001 | 0.008 | 0.003 | 0.002 | 0.004 | 0.008 | | 0.002 | 0.003 | 0.009 | 0.004 | 0.003 | 0.003 | 0.002 | 0.002 | 0.002 | 0.002 | AND THE PROPERTY OF THE PROPER | 0.002 | 0.002 | 0.009 | 0.004 | Dissolved Orthophosphate (mg P/L) |
| 10 | 0.064 | 0.017 | 0.025 | 0.017 | 0.031 | 0.064 | 0.027 | 0.020 | 0.017 | 0.017 | 0.026 | 0.021 | 0.058 | 0.034 | 0.024 | | And the state of t | | | | | | | | | | *************************************** | | AND THE RESERVE AND THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN THE PERSON NAMED | | Total Phosphorus (mg/L) |
| 10 | 19.83 | 14.44 | 17.56 | 2.01 | 17.16 | 18.75 | 18.94 | 14.44 | 14.44 | 14.87 | 16.44 | 17.42 | 19.83 | 18.76 | 17.69 | The state of the s | And the state of t | | | | | | manusch date general eine geber des gebrechte | | | | Annual Constitution of the Party of the Constitution of the Consti | | | | Total Organic Carbon (mg/L) |

Table A5. Water Quality Data Collected Using Autosamplers at Station L28IS from March 1998 through September 1998.

| | Saskyonin (Syr. V. 17) | the contract of the second sec | Comments of the Comments of th |
|---------------------|------------------------|--|--|
| Date Sampled | Total Nitrogen (mg/L) | Total Phosphorus (mg/L) | Total Organic Carbon (mg/L) |
| 03/13/1998 | 0.913 | 0.043 | 18.31 |
| 03/20/1998 | 0.938 | 0.041 | 18.37 |
| 03/27/1998 | 0.923 | 0.043 | 18.84 |
| 04/03/1998 | 0.988 | 0.045 | 20.14 |
| 04/10/1998 | 0.922 | 0.051 | 20.34 |
| 04/17/1998 | 0.844 | 0.072 | 21.16 |
| 04/28/1998 | 0.895 | 0.095 | 22.65 |
| 05/01/1998 | 1.099 | 0.052 | 26.50 |
| 05/08/1998 | 1.077 | 0.052 | 21.18 |
| 05/15/1998 | 1.026 | 0.001 | 43.16 |
| 05/22/1998 | 1.154 | 0.030 | 22.89 |
| 05/29/1998 | 1,180 | 0.066 | 20.08 |
| 06/05/1998 | 0.989 | 0.028 | 18.37 |
| 06/12/1998 | 1.047 | 0.048 | 20.00 |
| 06/19/1998 | 1.189 | 0.069 | 20.27 |
| 06/26/1998 | 1.100 | 0.073 | Annual III |
| 07/03/1998 | 0.957 | 0.058 | |
| 07/10/1998 | 0.572 | 0.061 | |
| 07/17/1998 | 1.762 | 0.047 | |
| 08/07/1998 | 1.173 | 0.069 | |
| 08/14/1998 | 1.016 | 0.046 | |
| 08/21/1998 | 0.730 | 0.026 | The state of the s |
| 09/04/1998 | 0.970 | 0.072 | |
| 09/11/1998 | 1.183 | 0.064 | |
| 09/18/1998 | 1.078 | 0.081 | |
| Меап | 1.029 | 0.053 | 22.15 |
| Standard Deviation | 0.211 | 0.020 | 6.19 |
| Median | 1.016 | 0.052 | 20.27 |
| Minimum | 0.572 | 0.001 | 18,31 |
| Maximum | 1.762 | 0.095 | 43.16 |
| No. of Observations | 25 | 25 | 15 |

<u>(</u>

.